

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Splice box, design: 19" rack patch module, degree of protection: IP20, material: Metal, connection method: Splicing, housing size: 1, color: gray



## Product description

FDX 20 series 19" splice boxes, 1 RU, with removable drawer, for 12x SC duplex OM4, pink, completely ready to splice (correctly pre-mounted: 12 SC duplex couplings, 12 filler plugs, 24 pigtails, 2 cassettes, 2 combs, 1 cassette cover).  
4 cable entries (rear) incl. 2 Pg16 cable glands, 2 sealing caps, and 19" mounting set.

## Your advantages

- Intuitive front-panel operation and clear control cabinet layout thanks to uniform design
- Flexible DIN rail mounting possible in six positioning directions
- Suitable for industrial applications
- Reduced installation time with plug-and-play
- Pin assignment straight in line in a link
- Continuously reliable data connection, thanks to extensively tested components
- Snap-on mounting on standard DIN rails NS 35/7.5 or NS 35/15
- Transmission rate up to 1000 Mbps

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1145406       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AB15          |
| Product key                          | ABNGBA        |
| GTIN                                 | 4063151135904 |
| Weight per piece (including packing) | 3,043.3 g     |
| Weight per piece (excluding packing) | 2,675.5 g     |
| Customs tariff number                | 85367000      |
| Country of origin                    | DE            |

## Technical data

### Product properties

|                              |                         |
|------------------------------|-------------------------|
| Product type                 | Network distributor box |
| Series                       | FDX 20 series           |
| Type                         | 19" rack patch module   |
| Connection profile           | SC-Duplex               |
| No. of cable outlets         | 4                       |
| No. of conductors            | 24                      |
| Number of module slots       | 12                      |
| Number of slots              | 24                      |
| Type of the screw connection | 2x Pg16                 |
| Protective cover             | yes                     |

### Electrical properties

|                     |          |
|---------------------|----------|
| Attenuation         | ≤ 0.3 dB |
| Transmission medium | FO       |

### Connection data

#### Connection technology

|                   |          |
|-------------------|----------|
| Connection method | Splicing |
|-------------------|----------|

### Dimensions

|        |          |
|--------|----------|
| Width  | 480 mm   |
| Height | 44.45 mm |
| Depth  | 280 mm   |

#### Mechanical characteristics

|                  |         |
|------------------|---------|
| Ferrule diameter | 2.50 mm |
|------------------|---------|

### Material specifications

|                                        |                     |
|----------------------------------------|---------------------|
| Color                                  | gray                |
| Flammability rating according to UL 94 | V0                  |
| Ferrule material                       | Zirconia ceramics   |
| Housing material                       | Metal               |
| Housing surface material               | Powder-coated, gray |

### Cable/line

|                          |                                |
|--------------------------|--------------------------------|
| Cable type               | Fiberglass                     |
| Cable type               | Loose Tube                     |
| Cable structure          | semi-loose compact wires (STB) |
| External cable diameter  | 7 mm ... 12 mm                 |
| External cable diameter  | 6 mm ... 12 mm                 |
| Individual wire diameter | 900 µm                         |

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

|                    |             |
|--------------------|-------------|
| Single wire, color | color coded |
| Whip length        | 750 mm      |
| Halogen-free       | yes         |
| Flame resistance   | yes         |

## FO cable

|                     |                                 |
|---------------------|---------------------------------|
| Number of fibers    | 24                              |
| Fiber               | GOF                             |
| Fiber type          | Multi-mode 50/125 µm fiberglass |
| Attenuation         | ≤ 0.3 dB (at 850 nm / 1300 nm)  |
| Return Loss         | ≥ 35 dB (at 850 nm / 1300 nm)   |
| Transmission medium | FO                              |

## Mechanical properties

### Mechanical data

|                              |         |
|------------------------------|---------|
| Type of the screw connection | 2x Pg16 |
| Insertion/withdrawal cycles  | ≥ 500   |
| Smallest bending radius      | 30 mm   |

## Characteristics

|             |          |
|-------------|----------|
| Attenuation | ≤ 0.3 dB |
|-------------|----------|

## Environmental and real-life conditions

### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Degree of protection                    | IP20             |
| Ambient temperature (operation)         | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Ambient temperature (assembly)          | 0 °C ... 50 °C   |
| Resistance to UV radiation              | yes              |

## Standards and regulations

|                  |     |
|------------------|-----|
| Flame resistance | yes |
|------------------|-----|

## Mounting

|               |                   |
|---------------|-------------------|
| Mounting type | 19" rack mounting |
|---------------|-------------------|



1145406

<https://www.phoenixcontact.com/us/products/1145406>

Classifications

ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 19170113 |
| ECLASS-12.0 | 19170113 |
| ECLASS-13.0 | 19170113 |

ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002699 |
|----------|----------|

UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 43223300 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

## Mandatory accessories

### FOC-SHRINKSPLICE-PROTECT - Shrink splice protection

1019676

<https://www.phoenixcontact.com/us/products/1019676>



Shrink splice protection, design: Straight, degree of protection: IP20, cable outlet: above and below, color: transparent

---

### FOC-CRIMPSPLICE-PROTECT - Crimp splice protection

1019678

<https://www.phoenixcontact.com/us/products/1019678>



Crimp splice protection, design: Straight, degree of protection: IP20, connection method: Crimp connection, cable outlet: above and below, color: Bare metallic

---

## Accessories

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box

1145406

<https://www.phoenixcontact.com/us/products/1145406>




## FOC-SC:PA-SC:PA-OM4:D01/1 - FO patch cable

1115424

<https://www.phoenixcontact.com/us/products/1115424>

Multi-mode OM4 duplex jumper, SC-SC, UPC polishing, length 1 m




---

## FOC-LC:PA-SC:PA-OM4:D01/1 - FO patch cable

1115601

<https://www.phoenixcontact.com/us/products/1115601>

Multi-mode OM4 duplex jumper, LC-SC, UPC polishing, length 1 m



# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box

1145406

<https://www.phoenixcontact.com/us/products/1145406>




## FOC-SC:PA-SC:PA-OM4:D01/2 - FO patch cable

1115423

<https://www.phoenixcontact.com/us/products/1115423>

Multi-mode OM4 duplex jumper, SC-SC, UPC polishing, length 2 m




---

## FOC-LC:PA-SC:PA-OM4:D01/2 - FO patch cable

1115600

<https://www.phoenixcontact.com/us/products/1115600>

Multi-mode OM4 duplex jumper, LC-SC, UPC polishing, length 2 m



# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box

1145406

<https://www.phoenixcontact.com/us/products/1145406>




## FOC-SC:PA-SC:PA-OM4:D01/5 - FO patch cable

1115418

<https://www.phoenixcontact.com/us/products/1115418>

Multi-mode OM4 duplex jumper, SC-SC, UPC polishing, length 5 m




---

## FOC-LC:PA-SC:PA-OM4:D01/5 - FO patch cable

1115598

<https://www.phoenixcontact.com/us/products/1115598>

Multi-mode OM4 duplex jumper, LC-SC, UPC polishing, length 5 m



# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

## FOC-PT9:SC-OM4/2.5 - Fiber optic cable

1208112

<https://www.phoenixcontact.com/us/products/1208112>

Fiber optic cable, design: SC, degree of protection: IP20, cable length: 2.5 m, number of positions: 12, 10 Gbps, connection method: SC, cable outlet: straight, color: violet



---

## FOC-ADAPTER:SCD/SCD-OM4 - Fiber optic coupling

1208085

<https://www.phoenixcontact.com/us/products/1208085>

Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Plastic, connection method: Coupling, cable outlet: straight, color: violet, Ethernet



# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

## FOC-OE-OE-GMB-U-OM4-12/... - FO cable

1286209

<https://www.phoenixcontact.com/us/products/1286209>



GOF universal cable, 12-wire, mini breakout cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

---

## FOC-OE-OE-GL-U-OM4-12/... - FO cable

1286220

<https://www.phoenixcontact.com/us/products/1286220>



GOF universal cable, 12-wire, loose tube cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

## FOC-OE-OE-GMB-U-OM4-24/... - FO cable

1286208

<https://www.phoenixcontact.com/us/products/1286208>



GOF universal cable, 24-wire, mini breakout cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

---

## FOC-OE-OE-GL-U-OM4-24/... - FO cable

1286211

<https://www.phoenixcontact.com/us/products/1286211>



GOF universal cable, 24-wire, loose tube cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

# FOC-FDX20-FR19-SCD12-OM4-PT9 - Splice box



1145406

<https://www.phoenixcontact.com/us/products/1145406>

## FOC-ADAPTER:SCD/SCD-MM-ME - Fiber optic coupling

1208083

<https://www.phoenixcontact.com/us/products/1208083>



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Metal, connection method: Coupling, cable outlet: straight, color: silver/matt, Ethernet

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)