

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Splice box, design: 19" rack patch module, degree of protection: IP20, material: Metal, connection method: Splicing, housing size: 1, color: gray



## Product description

FDX 20 series 19" splice boxes, 1 RU, with removable drawer, for 24x ST duplex OS2, metal, completely ready to splice (correctly pre-mounted: 24 ST duplex couplings, 24 filler plugs, 48 pigtails, 4 cassettes, 4 combs, 1 cassette cover).  
4 cable entries (rear) incl. 2 Pg16 cable glands, 2 sealing caps, and 19" mounting set.

## Your advantages

- Intuitive front-panel operation and clear control cabinet layout thanks to uniform design
- Flexible DIN rail mounting possible in six positioning directions
- Suitable for industrial applications
- Reduced installation time with plug-and-play
- Pin assignment straight in line in a link
- Continuously reliable data connection, thanks to extensively tested components
- Snap-on mounting on standard DIN rails NS 35/7.5 or NS 35/15
- Transmission rate up to 1000 Mbps

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1145392       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AB15          |
| Product key                          | ABNGBA        |
| GTIN                                 | 4063151135737 |
| Weight per piece (including packing) | 3,390 g       |
| Weight per piece (excluding packing) | 2,675.5 g     |
| Customs tariff number                | 85367000      |
| Country of origin                    | DE            |

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## Technical data

### Product properties

|                              |                         |
|------------------------------|-------------------------|
| Product type                 | Network distributor box |
| Series                       | FDX 20 series           |
| Type                         | 19" rack patch module   |
| Connection profile           | ST-Duplex               |
| No. of cable outlets         | 4                       |
| No. of conductors            | 48                      |
| Number of module slots       | 24                      |
| Number of slots              | 48                      |
| Type of the screw connection | 2x Pg16                 |
| Protective cover             | yes                     |

### Electrical properties

|                     |          |
|---------------------|----------|
| Attenuation         | ≤ 0.3 dB |
| Transmission medium | FO       |

### Connection data

#### Connection technology

|                   |          |
|-------------------|----------|
| Connection method | Splicing |
|-------------------|----------|

### Dimensions

|        |          |
|--------|----------|
| Width  | 480 mm   |
| Height | 44.45 mm |
| Depth  | 280 mm   |

#### Mechanical characteristics

|                  |         |
|------------------|---------|
| Ferrule diameter | 2.50 mm |
|------------------|---------|

### Material specifications

|                                        |                     |
|----------------------------------------|---------------------|
| Color                                  | gray                |
| Flammability rating according to UL 94 | V0                  |
| Ferrule material                       | Zirconia ceramics   |
| Housing material                       | Metal               |
| Housing surface material               | Powder-coated, gray |

### Cable/line

|                                |                                |
|--------------------------------|--------------------------------|
| Cable type                     | Fiberglass                     |
| Cable type                     | Loose Tube                     |
| Cable structure                | semi-loose compact wires (STB) |
| External cable diameter        | 7 mm ... 12 mm                 |
| External cable diameter        | 6 mm ... 12 mm                 |
| Wire diameter incl. insulation | 900 µm                         |

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

|                          |             |
|--------------------------|-------------|
| Individual wire diameter | 900 µm      |
| Single wire, color       | color coded |
| Whip length              | 750 mm      |
| Halogen-free             | yes         |
| Flame resistance         | yes         |

## FO cable

|                     |                                  |
|---------------------|----------------------------------|
| Number of fibers    | 48                               |
| Fiber               | GOF                              |
| Fiber type          | Single mode fiberglass, 9/125 µm |
| Attenuation         | ≤ 0.3 dB (at 1310 nm / 1550 nm)  |
| Return Loss         | ≥ 50 dB (at 1310 nm / 1550 nm)   |
| Transmission medium | FO                               |

## Mechanical properties

### Mechanical data

|                              |         |
|------------------------------|---------|
| Type of the screw connection | 2x Pg16 |
| Insertion/withdrawal cycles  | ≥ 500   |
| Smallest bending radius      | 30 mm   |

## Characteristics

|             |          |
|-------------|----------|
| Attenuation | ≤ 0.3 dB |
|-------------|----------|

## Environmental and real-life conditions

### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Degree of protection                    | IP20             |
| Ambient temperature (operation)         | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Ambient temperature (assembly)          | 0 °C ... 50 °C   |
| Resistance to UV radiation              | yes              |

## Standards and regulations

|                  |     |
|------------------|-----|
| Flame resistance | yes |
|------------------|-----|

## Mounting

|               |                   |
|---------------|-------------------|
| Mounting type | 19" rack mounting |
|---------------|-------------------|

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 19170113 |
| ECLASS-12.0 | 19170113 |
| ECLASS-13.0 | 19170113 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002699 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 43223300 |
|-------------|----------|



1145392

<https://www.phoenixcontact.com/us/products/1145392>

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## Mandatory accessories

### FOC-SHRINKSPLICE-PROTECT - Shrink splice protection

1019676

<https://www.phoenixcontact.com/us/products/1019676>



Shrink splice protection, design: Straight, degree of protection: IP20, cable outlet: above and below, color: transparent

---

### FOC-CRIMPSPLICE-PROTECT - Crimp splice protection

1019678

<https://www.phoenixcontact.com/us/products/1019678>



Crimp splice protection, design: Straight, degree of protection: IP20, connection method: Crimp connection, cable outlet: above and below, color: Bare metallic

---

## Accessories

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392


<https://www.phoenixcontact.com/us/products/1145392>

## FOC-ST:PA-ST:PA-OS2:D01/1 - FO patch cable

1115565

<https://www.phoenixcontact.com/us/products/1115565>

Single-mode OS2 duplex jumper, ST-ST, UPC polishing, length 1 m




---

## FOC-ST:PA-SC:PA-OS2:D01/1 - FO patch cable

1115582

<https://www.phoenixcontact.com/us/products/1115582>

Single-mode OS2 duplex jumper, ST-SC, UPC polishing, length 1 m



# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## FOC-LC:PA-ST:PA-OS2:D01/1 - FO patch cable

1115596

<https://www.phoenixcontact.com/us/products/1115596>

Single-mode OS2 duplex jumper, LC-ST, UPC polishing, length 1 m




---

## FOC-ST:PA-ST:PA-OS2:D01/2 - FO patch cable

1115564

<https://www.phoenixcontact.com/us/products/1115564>

Single-mode OS2 duplex jumper, ST-ST, UPC polishing, length 2 m



# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box

1145392

<https://www.phoenixcontact.com/us/products/1145392>




## FOC-ST:PA-SC:PA-OS2:D01/2 - FO patch cable

1115581

<https://www.phoenixcontact.com/us/products/1115581>

Single-mode OS2 duplex jumper, ST-SC, UPC polishing, length 2 m



---

## FOC-LC:PA-ST:PA-OS2:D01/2 - FO patch cable

1115595

<https://www.phoenixcontact.com/us/products/1115595>

Single-mode OS2 duplex jumper, LC-ST, UPC polishing, length 2 m



# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392


<https://www.phoenixcontact.com/us/products/1145392>

## FOC-ST:PA-ST:PA-OS2:D01/5 - FO patch cable

1115562

<https://www.phoenixcontact.com/us/products/1115562>

Single-mode OS2 duplex jumper, ST-ST, UPC polishing, length 5 m




---

## FOC-ST:PA-SC:PA-OS2:D01/5 - FO patch cable

1115579

<https://www.phoenixcontact.com/us/products/1115579>

Single-mode OS2 duplex jumper, ST-SC, UPC polishing, length 5 m



# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## FOC-LC:PA-ST:PA-OS2:D01/5 - FO patch cable

1115592

<https://www.phoenixcontact.com/us/products/1115592>

Single-mode OS2 duplex jumper, LC-ST, UPC polishing, length 5 m




---

## FOC-PT9:SC-OSP/2.5 - Fiber optic cable

1208113

<https://www.phoenixcontact.com/us/products/1208113>



Fiber optic cable, design: SC, degree of protection: IP20, cable length: 2.5 m, number of positions: 12, 100 Gbps, material: Plastic, connection method: SC, cable outlet: straight, color: blue

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## FOC-PT9:SC-OSA/2.5 - Fiber optic cable

1208114

<https://www.phoenixcontact.com/us/products/1208114>

Fiber optic cable, design: SC, degree of protection: IP20, cable length: 2.5 m, number of positions: 12, 100 Gbps, connection method: SC, cable outlet: straight, color: green



---

## FOC-ADAPTER:SCD/SCD-OSP - Fiber optic coupling

1208086

<https://www.phoenixcontact.com/us/products/1208086>

Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Plastic, connection method: Coupling, cable outlet: straight, color: blue



# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392


<https://www.phoenixcontact.com/us/products/1145392>

## FOC-ADAPTER:SCD/SCD-OSA - Fiber optic coupling

1208088

<https://www.phoenixcontact.com/us/products/1208088>

Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Plastic, connection method: Coupling, cable outlet: straight, color: green



---

## FOC-OE-OE-GL-U-OS2-24/... - FO cable

1286210

<https://www.phoenixcontact.com/us/products/1286210>



GOF universal cable, 24-wire, loose tube cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

# FOC-FDX20-FR19-STD24-OSP-PT9 - Splice box



1145392

<https://www.phoenixcontact.com/us/products/1145392>

## FOC-OE-OE-GL-U-OS2-12/... - FO cable

1286219

<https://www.phoenixcontact.com/us/products/1286219>



GOF universal cable, 12-wire, loose tube cable for fixed installation, non-metallic rodent protection, can be easily stripped, UV-resistant, high mechanical and thermal stability, low smoke, halogen-free and self-extinguishing, improved tread resistance, longitudinally and transversely watertight

---

## FOC-ADAPTER:STD/SCD-SM - Fiber optic coupling

1208098

<https://www.phoenixcontact.com/us/products/1208098>



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Metal, connection method: Coupling, cable outlet: straight, color: silver/matt

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)