

Agastat

TE Internal #: 2-1423164-2

Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) 5 – 50 seconds, 10A Contact Current Rating, Off-Delay, Chassis

[View on TE.com >](#)

Relays & Contactors > Relays > Time Delay Relays

Type of Control: **Knob**Input Voltage: **125 VDC**Timing Range (Off-Time): **5 – 50 seconds**Contact Current Rating: **10 A**Mode of Operation: **Off-Delay****Features****Configuration Features**

Contact Arrangement	2 Form C, DPDT, 2 C/O
---------------------	-----------------------

Electrical Characteristics

Input Voltage	125 VDC
---------------	---------

Contact Current Rating	10 A
------------------------	------

Termination Features

Relay Connection Type	Terminals
-----------------------	-----------

Terminal Configuration	Screw Terminals
------------------------	-----------------

Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
-------------------------------	-------------------

Product Mount Type	Chassis
--------------------	---------

Dimensions

Product Width	82.55 mm[3.25 in]
---------------	-------------------

Product Length	114.8 mm[4.52 in]
----------------	-------------------

Product Height	78.4 mm[3.09 in]
----------------	------------------

Usage Conditions

Operating Temperature Range	-30 – 75 °C
-----------------------------	-------------

Operation/Application



Repeatability (Max)	±5%
Actuating System	DC
Type of Control	Knob
Timing Range (Off-Time)	5 – 50 seconds
Mode of Operation	Off-Delay

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Cadmium oxide (10% in Component (Contact)) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought

