



Scan the QR code and visit the product page



Code	TK.LB.D0290S.AEC	Safety level	Danger
Dimensions (H x L)	34 mm x 70 mm (1,3" x 2,7")	Version	Small
Material	PVC base with adhesive liner and protective layer	Temperatures ⁽¹⁾	-40°C/+95°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages ⁽²⁾	Inglese		
Message ⁽³⁾	EN: DO NOT DISCONNECT UNDER LOAD IT: NON SCOLLEGARE SOTTO CARICO		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z355, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CE Code), CSA C22.2 No.286		
Standards Construction	ANSI Z355, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.