

3-Outlet Surge Protector with 2 USB Ports, 10 ft. (3.05 m) Cord - 510 Joules, Desk Clamp, White Housing

MODEL NUMBER: TLP310USBCW



Clamps safely to your workstation to protect your electronics against surges and charge your mobile devices.

Features

510-Joule Surge Protection for Home or Office Electronics The 510-joule rating means your computer, printer, scanner, external hard drive and other sensitive electronic components are protected against strong surges and spikes.

This power surge protector with USB ports features full normal mode (H-N) and common mode (N-G/H-G) line surge suppression. It filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss and exceeds IEEE 587 Category A and B surge suppression specifications.

Charges a Wide Range of Electronic Devices This 10-ft. (3.05 m) surge protector features two USB ports that produce 3.1A of combined power to charge your mobile devices, including smartphones, tablets and MP3 players. A top storage shelf holds smartphones and other small devices while they're charging.

Fits Effortlessly Into Your Workstation This 3-plug surge protector mounts to a clamp that attaches to most desks, tables and flat surfaces, bringing power and device charging to your desktop. Clamps adjusts from .59 to 1.77". The 10-ft. (3.05 m) power cord has a NEMA 5-15P plug and fits through the back of the clamp to reduce cable clutter.

Lifetime Limited Warranty and Ultimate Lifetime Insurance This three-outlet surge protector comes with a lifetime limited warranty and is backed by \$20,000 Ultimate Lifetime Insurance for any connected components damaged by a power surge (U.S., Canada and Puerto Rico only).

Specifications

| OVERVIEW | |
|--------------|-----------------|
| UPC Code | 037332224897 |
| Product Type | Surge Protector |

Highlights

- Clamps firmly to most desks, tables and flat surfaces. Clamp adjusts from .59 to 1.77"
- 3 NEMA 5-15R outlets power most computers and peripherals
- 2 USB ports (3.1A total) for charging mobile devices
- 510 joules of surge suppression
- 10-ft. (3.05 m) power cord reaches distant AC outlets

Applications

- Supplies power and charging in a limited amount of space, making it perfect for homes and offices, as well as college dorms and hotel rooms
- Safeguards your computer, printer and peripherals from dangerous surges
- Shields TVs, DVD players, video game consoles, streaming media players, sound systems and device chargers from surges
- Charges your equipment while keeping it safe

Package Includes

- TLP310USBCW Protect It! 3-Outlet Surge Protector
- Desk clamp
- Mounting hardware
- Owner's manual



Powering Business Worldwide



| | |
|--|------------------------------|
| Charging Form Factor | Strip |
| Device Compatibility | Phone; Tablet; Amazon Kindle |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V |
| Input Cord Length Details | Strip |
| Input Cord Gauge (AWG) | 14 |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Details | SJT |
| Input Cord Length (ft.) | 10 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 3.05 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| Output Receptacles | (4) 5-15R |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (3) Yes |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Diagnostic LED Details | X1 Green LED - Protected |
| CHARGING | |
| Number of Charging Ports | 2 |
| Total Charging Watts | 15.5 |
| Charging Method | USB |
| Charging Port Type | USB A (FEMALE) |
| Charging Ports / Amps | (2) 3.1A |
| Overcharge Protection | No |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 510 |
| AC Suppression Response Time | < 1 ns |



Powering Business Worldwide



| | |
|--|---|
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating | 1000 |
| EMI / RFI Filtering | Yes |
| Immunity | Conforms to IEE 587/ANSI C62.41 |
| Automatic Shut-Off | No |
| DATALINE SURGE SUPPRESSION | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| PHYSICAL | |
| Material of Construction | Plastic |
| Power Cord Color | Gray |
| Included Mounting Accessories | Mounting hardware |
| Mounting Holes or Slots | No |
| Receptacle Color | White |
| Shipping Dimensions (hwd / in.) | 7.40 x 4.10 x 5.40 |
| Shipping Weight (kg) | 1.18 |
| Unit Dimensions (hwd / in.) | 1.940 x 1.760 x 5.510 |
| Unit Dimensions (hwd / cm) | 4.93 x 4.47 x 14.7 |
| Unit Weight (lbs.) | 2.34 |
| Unit Weight (kg) | 1.06 |
| FEATURES & SPECIFICATIONS | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| GaN Technology | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | UL 1449; UL 962A |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 Ultimate Lifetime Insurance |



Powering Business Worldwide



1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.