


Technical data for standard (FL)  
Crimp contacts not supplied with connector. Contacts must be ordered separately.

5	2	Funnel	MW 3.1 / Steel	tin plated
4	1	Guide plate	Steel	nickel plated
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PA66 (-55°C to +115°C) acc. UL94V-0	black
1	1	Insulator front part	PBT acc. UL94V-0	black
No.	St.	Part	Type Description/Material	Surface plating/Colour/Class

FUNCTIONAL SYMBOLS  ▽ = 0  ▽ = 0  ▽ = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							
	DIMENSION UNITS <b>mm</b>		SCALE <b>2:1</b>	MEASUREMENTS WITHOUT TOLERANCE ACC. TO ISO 2768-m		<b>molex</b>		
			CURRENT REVISION		FCT D-Sub Crimp Connector			
			DRWN: DRAWN BY msteinbrueck 11-05-2023					
			APPR: APPR BY fvetter 11-05-2023					
	2 24130		INITIAL REVISION		PRODUCT CUSTOMER DRAWING			
	1		DRWN: DRAWN BY MTeubel 05-02-2019		MATERIAL NUMBER		REVISION	
	REV. CH.-NO.		APPR: APPR BY tschneider01 05-02-2019		1731071445		2	
	REPLACEMENT FOR:		FRIST ANGLE PROJECTION 	DRAWING <b>A3-SIZE</b>	DOCUMENT NUMBER <b>FL36W4S7-3094</b>		CUSTOMER GENERAL MARKET	SHEET NUMBER 1 OF 1