

Part Number: 2147632122

Product Description: Pre-Crimped Lead Micro-Fit 3.0 Male-to-Pigtail, Tin (Sn) Plating,

150.00mm Length, 18 AWG, Red

Status: Active

Series Number: 214763

**Product Category :** Power and Signal Cable Assemblies

#### **Documents & Resources**

#### **Drawings**

Drawing 2147632122\_sd.pdf

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | •   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **EU RoHS Certificate of Compliance**

#### **Part Details**

## General

| Status                 | Active   |
|------------------------|--|
| Category               | Power and Signal Cable Assemblies  |
| Series                 | 214763   |
| Description            | Pre-Crimped Lead Micro-Fit 3.0<br>Male-to-Pigtail, Tin (Sn) Plating,<br>150.00mm Length, 18 AWG, Red |
| Application            | Power, Wire-to-Wire  |
| Assembly Configuration | Pre-crimped Lead Only  |
| Connector to Connector | Micro-Fit 3.0 Term-to-Pigtail  |
| Keyword                | Pre-Crimped Leads  |
| Product Family         | Off-the-Shelf Pre-Crimped Leads  |
| Product Name           | Micro-Fit 3.0  |
| UPC                    | 193264575336   |

# Electrical

| Current - Maximum per Contact | 8.5A |
|-------------------------------|------|
|-------------------------------|------|

# Physical

| Cable Length                   | 150.00mm             |
|--------------------------------|----------------------|
| Circuits (Loaded)              | 1                    |
| Circuits (maximum)             | 1                    |
| Color - Resin                  | Red                  |
| Gender                         | Male-Pigtail         |
| Material - Metal               | Phosphor Bronze      |
| Material - Plating Mating      | Tin                  |
| Material - Plating Termination | Tin                  |
| Net Weight                     | 1.786/g              |
| Packaging Type                 | Bag                  |
| Plating min - Mating           | 1.016µm              |
| Plating min - Termination      | 1.016µm              |
| Single Ended                   | Yes                  |
| Termination Interface Style    | Crimp or Compression |
| Wire/Cable Type                | UL 10002             |
| Wire Insulation Diameter       | 1.85mm max.          |

| Wire Size (AWG) | 18 |
|-----------------|----|
|-----------------|----|

# Use with Part(s)

| Description                               | Part Number |
|---|-------------|
| Micro-Fit 3.0 Dual Row Plug<br>Housings   | 43020       |
| Micro-Fit 3.0 Single Row Plug<br>Housings | 43640       |
| Micro-Fit BMI Dual Row Plug<br>Housings   | 44300       |
| Micro-Fit BMI Single Row Plug<br>Housings | 46625       |

This document was generated on May 27, 2024