

1379217-3  ACTIVE

MQS

TE Internal #: 1379217-3

Housing for Female Terminals, Wire-to-Board / Wire-to-Wire, 5 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Power & Signal, MQS

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector System: **Wire-to-Board, Wire-to-Wire**

Number of Positions: **5**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **2.54 mm [.1 in]**

Sealable: **No**

[All MQS, CONNECTOR HOUSING \(435\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Locking Lance

Configuration Features

Number of Positions	5
Number of Rows	1

Electrical Characteristics

Operating Voltage	16 VDC
-------------------	--------

Nominal Voltage Architecture 12 V, 16 V

Body Features

Cable Exit Angle 180°

Primary Product Color Black

Connector & Keying Code Neutral

Contact Features

Contact Size .63mm, 2.8mm

Contact Type Receptacle

Mating Tab Width .63 mm, 2.8 mm[.025 in][.11 in]

Contact Current Rating (Max) 7.5 A, 35 A

Mechanical Attachment

Terminal Position Assurance Yes

Strain Relief Without

Mating Alignment Type Keyed

Mating Alignment With

Connector Mounting Type Cable Mount (Free-Hanging)

Housing Features

Housing Material PBT GF

Centerline (Pitch) 2.54 mm[.1 in]

Dimensions

Product Length 19 mm[.748 in]

Usage Conditions

Operating Temperature (Max) 100 °C[212 °F]

Operating Temperature Range -40 - 100 °C[-40 - 212 °F]

Operation/Application

Circuit Application Power & Signal

Industry Standards

UL Flammability Rating UL 94HB

Other

Serviceable Yes

Connector Position Assurance Capable No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



Also in the Series | MQS



Customers Also Bought





Documents

Product Drawings

5POS MIXED MQS REC COD Z

English

CAD Files

Customer View Model

[ENG_CVM_CVM_1379217-3_A.2d_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1379217-3_A.3d_jgs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1379217-3_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Micro Quadlok Interconnection System (MQS)

English

Product Specifications

2 WAY MPQ + 3 WAY MQS SOCKET HOUSING

English

Product Specification

English