

1SNK708062R0000


✓ ACTIVE

ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK708062R0000

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block,
Red, Product Spacing .315 in [8 mm], 2 Position, DIN Rail,
ENTRELEC SNK[View on TE.com >](#)

Connectors > Terminal Blocks & Strips > Modular Terminal Blocks

Block Function: **Feed-Through**Modular Terminal Block Product Type: **PI-Spring Terminal Block**Primary Product Color: **Red**Product Spacing: **8 mm [.315 in]**Number of Positions: **2**

Features

Product Type Features

| | |
|-------------------------------------|--------------------------|
| Modular Terminal Block Product Type | PI-Spring Terminal Block |
|-------------------------------------|--------------------------|

Configuration Features

| | |
|---------------------|------------------|
| Gauge Type | A5 & 3.9 mm Dia. |
| Number of Levels | 1 |
| Number of Circuits | 1 |
| Block Function | Feed-Through |
| Number of Positions | 2 |

Electrical Characteristics

| | |
|--|--------|
| Operating Voltage Rating (UL & CSA) (Max) - Main Circuit | 600 V |
| Impulse Withstanding Voltage Rating (IEC) | 8000 V |
| Voltage Rating (CSA) | 600 V |
| Current Rating (CSA) | 50 A |
| Power Loss | 1.3 W |
| Dielectric Withstanding Voltage (Max) | 2200 V |

| | |
|---|--------|
| Short-Time Withstanding Current Rating @ 1s | 720 A |
| Voltage Rating (IEC) | 1000 V |
| Current Rating (UL) | 50 A |
| Current Rating (IEC) | 41 A |

Body Features

| | |
|-----------------------|------------------|
| Product Weight | 11.8 g [.465 oz] |
| Primary Product Color | Red |

Mechanical Attachment

| | |
|-------------------------|-------------------|
| DIN Rail Mounting Type | TH35-15, TH35-7.5 |
| Connector Mounting Type | DIN Rail |

Housing Features

| | |
|------------------|-----------|
| Housing Material | Polyamide |
|------------------|-----------|

Dimensions

| | |
|---|--------------------------|
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp | .5 - 10 mm ² |
| Main Circuit Capacity - Twin Ferrule per Spring Clamp | .5 - 1.5 mm ² |
| Wire Stripping Length | 12.5 mm [.492 in] |
| Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp | .5 - 6 mm ² |
| Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp | 24 - 10 AWG |
| Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp | .5 - 6 mm ² |
| Tool Size | 3.5 mm [.138 in] |
| Product Depth | 41.9 mm |
| Product Length | 41.9 mm |
| Product Height | 57.5 mm |
| Product Spacing | 8 mm [.315 in] |

Usage Conditions

| | |
|--------------------------------|-----------------------------|
| Installation Temperature Range | -5 - 40 °C [23 - 104 °F] |
| Operating Temperature Range | -55 - 110 °C [-67 - 230 °F] |

Industry Standards

| | |
|------------------------|----------|
| IP Rating | IP20 |
| UL Flammability Rating | UL 94V-0 |

Product Compliance


For compliance documentation, visit the product page on [TE.com](https://te.com)>


| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts






Also in the Series

ENTRELEC SNK



Customers Also Bought



Documents

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_1SNK708062R0000_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK708062R0000_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK708062R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ENTRELEC Terminal Block - Master Catalog](#)

[ENTRELEC Terminal Block - Master Catalog](#)

English

[ZK6-RD](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

Agency Approvals

[Bureau Veritas Marine and Offshore Certificate](#)

English

1SNK708062R0000

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Red, Product
Spacing .315 in [8 mm], 2 Position, DIN Rail, ENTRELEC SNK

