



## PRO-IS-583

[Request Samples](#)[Check Inventory](#)

**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**

### Features

- Frequency coverage : 868 - 960, 1710 - 1990 MHz
- Thickness of 0.8 mm
- Linear Polarization
- Gain of up to 2.9 dBi
- Efficiency > 37%
- Easy integration using cable and connector
- Customizable cable and Connector options

### Applications

- LoRA/SigFox/3G/2G/GSM/ISM applications
- IoT, M2M
- Industrial, Infrastructure IoT
- Smart Metering
- Consumer electronics
- Wireless modules
- Video and surveillance
- Broadband cellular connectivity

### Product Image





PRO-IS-583

Request Samples



Check Inventory



**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**

## Electrical Specification

Parameter	Specification		Unit
Operating Frequency	868 ~ 960	1710 ~ 1990	MHz
Return Loss	< -3.5	< -3.6	dB
Polarization	Linear		
Peak Gain	2.9	1.9	dBi
Efficiency	>37	>51	%
Impedance	50	50	Ω

## Mechanical Specification

Parameter	Specification
Antenna Dimension	50 x 8 x 0.8 mm
Cable Type	Coaxial
Cable length	100 mm
Connector Type	MHF-4 (F)
Mounting Type	Adhesive Tape


## Environmental Specification

Parameter	Specification
Operating Temperature	-40°C to +85°C
MSL Level	1
RoHS/RoHS II Compliant	Yes

**PRO-IS-583**[Request Samples](#)[Check Inventory](#)

**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**


## Product Dimensions



Unit: mm

## Measurement Setup

The antenna measurements were done on a standard measurement fixture - the antenna mounted in an ABS plastic box, 150x150x45 mm, connected to a PCB, 120x50 mm, with the cable fully extended





**PRO-IS-583**

Request Samples



Check Inventory




50.0 x 8.0 x 0.8mm

**RoHS/RoHS II Compliant**



MSL Level = 1

## Return Loss



## Total Radiation Efficiency

## Maximum Radiation Gain



**PRO-IS-583**

Request Samples









Check Inventory



**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**







## Radiation Characteristics - 2D Pattern (900 MHz)



**PRO-IS-583**[Request Samples](#)[Check Inventory](#)

**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**







## Radiation Characteristics - 2D Pattern (1710 MHz)



**PRO-IS-583**[Request Samples](#)[Check Inventory](#)

**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**

## Radiation Characteristics - 2D Pattern (1990 MHz)





**PRO-IS-583**

Request Samples [\(>\)](#)

Check Inventory [\(>\)](#)

**50.0 x 8.0 x 0.8mm**  
**RoHS/RoHS II Compliant**  
**MSL Level = 1**

## Packaging Information

Pieces per bag: 100 pieces

**ATTENTION:** Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669  
Phone: 512-371-6159 | Fax: 512-351-8858  
For terms and conditions of sales, please visit:  
[www.abracon.com](http://www.abracon.com)

**REVISED: 11-22-21**

ABRACON IS  
ISO9001-2015  
CERTIFIED