

## HARTING outd. Cat6A 4x2xAWG26/7 PVC 50m



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 600 0541
Specification	HARTING outd. Cat6A 4x2xAWG26/7 PVC 50m
HARTING eCatalogue	<a href="https://b2b.harting.com/09456000541">https://b2b.harting.com/09456000541</a>

### Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)

### Version

Cable length	50 m
Number of cores	8
Core structure	4x 2x AWG 26/7

### Technical characteristics

Transmission characteristics	Cat. 6A Class E <sub>A</sub> up to 500 MHz
	10 Mbit/s
	100 Mbit/s
Data rate	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-20 ... +80 °C
Cable diameter	6.3 ... 6.9 mm
Minimum bending radius	8x Cable diameter (repeated bending) 4x Cable diameter (singular bending)
Conductor resistance @ 20 °C	≤290 Ω/km
Insulation resistance @ 20 °C	≥500 MΩ x km
Signal run time @ 20 °C	≤5.13 ns/m

## Technical characteristics

Impedance @ 100 MHz	100 Ω ±5 %
---------------------	------------

## Material properties

Material (cable)	PVC
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide

## Specifications and approvals

Specifications	UN/ECE-R 118 fire protection for rolling stock
----------------	--

## Commercial data

Packaging size	1
Net weight	2,400 g
Country of origin	Germany
European customs tariff number	85444995
GTIN	5713140273566
ETIM	EC003249
eCl@ss	27061801 Data and communication cable (copper)