

**1SNK805724R0000**

✓ ACTIVE

**ENTRELEC | ENTRELEC SNK**

TE Internal #: 1SNK805724R0000

Modular Terminal Blocks, Female Plug, Gray, Product Spacing .205 in [5.2 mm], 2 Position, -55 - 110 °C [-67 - 230 °F], ENTRELEC SNK

[View on TE.com >](#)

Connectors &gt; Terminal Blocks &amp; Strips &gt; Modular Terminal Blocks

Modular Terminal Block Product Type: **Female Plug**Primary Product Color: **Gray**Product Spacing: **5.2 mm [.205 in]**Number of Positions: **2**Operating Temperature Range: **-55 - 110 °C [-67 - 230 °F]**

## Features

### Product Type Features

Modular Terminal Block Product Type	Female Plug
-------------------------------------	-------------

### Configuration Features

Gauge Type	A2 / 2.3 mm Dia.
------------	------------------

Number of Poles	10
-----------------	----

Number of Positions	2
---------------------	---

### Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
--	-------

Impulse Withstanding Voltage Rating (IEC)	8000 V
---	--------

Current Rating (CSA)	22 A
----------------------	------

Power Loss	4 W
------------	-----

Short-Time Withstanding Current Rating @ 1s	300 A
---	-------

Voltage Rating (IEC)	1000 V
----------------------	--------

Current Rating (UL)	22 A
---------------------	------

Current Rating (IEC)	24 A
----------------------	------

### Body Features

Product Weight	27.7 g
----------------	--------

Primary Product Color	Gray
-----------------------	------

### Housing Features

## Housing Material

Polyamide

## Dimensions

Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	.2 - 4 mm <sup>2</sup>
Main Circuit Capacity - Twin Ferrule per Spring Clamp	.22 - .5 mm <sup>2</sup>
Wire Stripping Length	11 mm
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	.22 - 2.5 mm <sup>2</sup>
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	26 - 14 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.22 - 2.5 mm <sup>2</sup>
Tool Size	3.5 mm [.138 in]
Product Depth	36.2 mm
Product Length	18.5 mm
Product Height	19.1 mm
Product Spacing	5.2 mm [.205 in]

## Usage Conditions

Operating Temperature Range	-55 - 110 °C [-67 - 230 °F]
-----------------------------	-----------------------------

## Industry Standards

IP Rating	IP20
-----------	------

## Product Compliance

For compliance documentation, visit the product page on [TE.com](http://TE.com)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 1SNK805010R0000  
ZDK2.5-22



TE Part # 1SNK805015R0000  
ZDK2.5-11



TE Part # 1SNK805017R0000  
ZD2.5-22



TE Part # 1SNK805212R0000  
ZDK2.5-D2-PE



TE Part # 1SNK805213R0000  
ZDK2.5-D2



TE Part # 1SNK805214R0000  
ZDK2.5-D1



TE Part # 1SNK900660R0000  
PT-ZD



TE Part # 1SNK805014R0000  
ZDK2.5-21



TE Part # 1SNK805016R0000  
ZD2.5-11

Also in the Series | **ENTRELEC SNK**



Modular Terminal Blocks(320)





Terminal Block &amp; Strip Conducting Accessories(67)



Terminal Block &amp; Strip Insulating Accessories(31)

## Customers Also Bought

TE Part # 1SNK805010R0000  
ZDK2.5-22TE Part # 1SNA116540R2500  
PC8-4TE Part # 1SNA206683R0400  
AJS9-BLTE Part # 1SNA206720R1400  
AJS9-RDTE Part # 1SNK508311R0000  
ZS10-ST-T4TE Part # 1SNK705511R0000  
ZK2.5-T1TE Part # 1SNK705961R0000  
EK2.5-T3TE Part # 1SNK908902R0000  
JB8-2-R1TE Part # 1SNA167932R1500  
COR-C-R4-6.6TE Part # 1SNA167934R1700  
COR-C-R5-6.6

## Documents

### CAD Files

[3D PDF](#)

3D

### Customer View Model

[ENG\\_CVM\\_CVM\\_1SNK805724R0000\\_A.2d\\_dxf.zip](#)  
English

### Customer View Model

[ENG\\_CVM\\_CVM\\_1SNK805724R0000\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1SNK805724R0000\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[CDK2.5-10](#)

English

Agency Approvals

[Bureau Veritas Marine and Offshore Certificate](#)

English