

| | | | | | | | |
|--|---|--------------------------|---|----------------|-----------------|----------------|------------|
| APPLICABLE STANDARD | | | | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -25°C TO +85°C | STORAGE TEMPERATURE RANGE | -25°C TO +60°C | | | |
| | | | | | | | |
| SPECIFICATIONS | | | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | | QT | | |
| CONSTRUCTION | | | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | | X | | |
| MECHANICAL CHARACTERISTICS | | | | | | | |
| VIBRATION | FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.  | | NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | | |
| SHOCK | 490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.  | | | | X | | |
| ENVIRONMENTAL CHARACTERISTICS | | | | | | | |
| THERMAL SHOCK | TEMP -55 → +5 TO +35 → +85 → +5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES. | | NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | | |
| CORROSION SALT MIST | EXPOSED AT 5 % SALT WATER, FOR 48 h. | | NO HEAVY CORROSION THAT LOSE FUNCTION. | | X | | |
| | | | | | | | |
| △ | COUNT | DESCRIPTION OF REVISIONS | | DESIGNED | CHECKED | DATE | |
| △ | | | | | | | |
| REMARK  EXAMINATION IS HELD WITH "DH60- * * P". Unless otherwise specified, refer to JIS C 5402 . | | | | | APPROVED | AO. SUZUKI | 09. 04. 27 |
| | | | | | CHECKED | MO. SHIMUYAMA | 09. 04. 24 |
| | | | | | DESIGNED | TS. ITO | 09. 04. 24 |
| | | | | | DRAWN | TS. ITO | 09. 04. 24 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | | DRAWING NO. | | ELC4-126895-00 | |
|  | SPECIFICATION SHEET | | | PART NO. | DH-LNA | | |
| | HIROSE ELECTRIC CO., LTD. | | | CODE NO. | CL244-0045-0-00 | | △ |