

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE		-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QTAT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MECHANICAL CHARACTERISTICS					
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. ①➤		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X—
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. ①➤			X—
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK		TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X—
CORROSION SALT MIST		EXPOSED AT 5 % SALT WATER, FOR 48 h.		NO HEAVY CORROSION THAT LOSE FUNCTION.	X—
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
⚠					
REMARK				APPROVED	A0. SUZUKI 09. 04. 27
①➤ EXAMINATION IS HELD WITH “DH60- * * P”.				CHECKED	MO. SHIMOYAMA 09. 04. 24
Unless otherwise specified, refer to JIS C 5402 .				DESIGNED	TS. ITO 09. 04. 24
				DRAWN	TS. ITO 09. 04. 24
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126530-00
HRS SPECIFICATION SHEET			PART NO.	DH-LNA-W16	
HIROSE ELECTRIC CO., LTD.			CODE NO.	CL244-0005-5-00	⚠ 1/1