


APPLICABLE STANDARD		MIL-STD-348B				
RATING	OPERATING TEMPERATURE RANGE	- 55°C TO + 105°C (95%RH MAX)		STORAGE TEMPERATURE RANGE	- 55°C TO + 50°C (95%RH MAX)	
	POWER	—W		CHARACTERISTIC IMPEDANCE	50 Ω (0 TO 40 GHz)	
	PECULIARITY	—		APPLICABLE CABLE	—	
SPECIFICATIONS						
ITEM	TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING	CONFIRMED VISUALLY.				—	—
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz).		CENTER CONTACT	4 mΩ MAX.	X	X
			OUTER CONTACT	2 mΩ MAX.	X	X
INSULATION RESISTANCE	500 V DC.		1000 MΩ MIN.		X	X
VOLTAGE PROOF	500 V AC FOR 1 min. CURRENT LEAKAGE 2mA MAX.		NO FLASHOVER OR BREAKDOWN.		X	X
VOLTAGE STANDING WAVE RATIO	FREQUENCY 0.04 TO 40 GHz ① TEST METHOD IS Back to Back	VSWR 1.10 MAX. (0.04 to 18 GHz) VSWR 1.15 MAX. (18 to 26.5 GHz) VSWR 1.30 MAX. (26.5 to 40 GHz)	X	—		
INSERTION LOSS	FREQUENCY ---- TO ---- GHz		--- dB MAX.		—	—
MECHANICAL CHARACTERISTICS						
CONTACT INSERTION AND EXTRACTION FORCES	0 Φ0.9195 -0.0025 BY STEEL GAUGE.		INSERTION FORCE --- N MAX.	—	—	
			EXTRACTION FORCE 0.4 N MIN.	X	X	
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE --- N MAX.	—	—	
			EXTRACTION FORCE --- N MIN.	—	—	
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.		1) CONTACT RESISTANCE: CENTER CONTACT 6 mΩ MAX. CHANGE OUTER CONTACT 4 mΩ MAX. CHANGE 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
VIBRATION	FREQUENCY 10 TO 2000 Hz SINGLE AMPLITUDE 0.75 mm, 196 m/s ² AT 12 CYCLES FOR 3 DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
SHOCK	1960 m/s ² DIRECTIONS OF PULSE 6 ms AT 3 TIMES FOR 3 DIRECTIONS.		2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT --N MAX.		1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.	—	—	
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT	EXPOSED AT -10 TO +65°C, 90 TO 98 % TOTAL 10 CYCLES (240h)		1) INSULATION RESISTANCE: 100 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 1000 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → ---- → +105 → ---- °C TIME 30 → 3 → 30 → 3 min UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48h.		NO HEAVY CORROSION.	X	—	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
①						
REMARK RoHS COMPLIANT Note ① Measurement state of Back to Back. Port1  Port2 Unless otherwise specified, refer to MIL-STD-202.				APPROVED	KY. SHIMIZU	15. 10. 22
				CHECKED	TO. KATAYAMA	15. 10. 22
				DESIGNED	NK. OOSAWA	15. 10. 22
				DRAWN	NK. OOSAWA	15. 10. 22
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-366760-12-00	
HRS	SPECIFICATION SHEET		PART NO.	HK-R-SR2-1(12)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL338-0003-0-12		① 1/1