

Relays & Contactors > Relays > Mil-Aero Relays > TO-5/.100 Grid Relays



Contact Arrangement: **2 Form C, DPDT, 2 C/O**

Input Voltage: **5 VDC**

Coil Voltage Rating: **5 VDC**

Coil Resistance: **50 Ω**

Coil Power Rating DC: **500 mW**

Features

Configuration Features

Coil Special Features	Coil Polarity Protection Diode, Coil Suppression Diode
-----------------------	--

Contact Arrangement	2 Form C, DPDT, 2 C/O
---------------------	-----------------------

Electrical Characteristics

Contact Current Rating	1 A
Contact Switching Voltage (Max)	28 VDC
Input Voltage	5 VDC
Coil Voltage Rating	5 VDC
Coil Resistance	50 Ω
Coil Power Rating DC	500 mW

Body Features

Enclosure Type	Hermetically Sealed
----------------	---------------------

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins

Usage Conditions

Operating Temperature Range	-65 - 125 °C
-----------------------------	--------------

Operation/Application

Vibration Resistance	30G's, 10 - 3000Hz
Actuating System	DC
Shock Resistance	75G's, 6ms
Coil Magnetic System	Non-Polarized, Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2-1617031-3
HFW1201K46 = M39016/6-209L

Customers Also Bought



TE Part # 6-1879021-5
SMW3 47R 5%



TE Part # 5106773-1
Z-PACK/A VF 110P




TE Part # 530347-3
KEY RIVET, BOX CONN



TE Part # 5569260-1
STK MJ ASSY,8POS,2X2,SHLD,CAT5



TE Part # 9-1879333-1
CPF0402 200K 0.1% 25PPM 5K RL



TE Part # 5-1617758-3
FCB-205-0227M=M83536/2-027M



TE Part # 1218124-2
15 POS,ASSY,PLUG,LOW PROF,109



TE Part # 8-2176529-8
3504G 3A 412R 1% 1K RL



TE Part # 6-535512-2
06 MODII HORZ DR CE EESS .100

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2-1617122-1_O.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1617122-1_O.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1617122-1_O.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

RELAY

English