

Temperature, humidity, CO2 transmitter with two relay and RS232 outputs

code: H6320

Temperature, humidity, CO2 level sensor with two output relays.



Green LED shines - CO2 concentration 0 to 1000 ppm

Yellow LED shines - CO2 concentration 1001 to 1200 ppm

Red LED shines - CO2 concentration 1201 ppm and more

Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
CO2 SENSOR	
Measuring range	0 to 2000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
RELAY OUTPUTS	
Quantity	2
Maximal voltage	50 V
Maximal current	2 A
Maximal power	60 VA
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	1x external CO ₂ sensor
Acoustic alarm	from built-in beeper - switchable
Output	RS232
Range of humidity sensor temperature compensation	all temperature range
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	ModBus RTU and Advantech ADAM compatible protocol

Power	9-30 Vdc
Protection class	IP65 electronics; IP40 sensors
Dimensions	136 x 213 x 45 mm; stem length 75mm
Weight	approx. 360 g
Warranty	3 years