




Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Terminal Block Connector Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **6**

Number of Rows: **1**

Wire Entry Angle: **180°**

Features

Product Type Features

Terminal Block Connector Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Wire Entry Location	Top
Stacking Configuration	Side Stackable
Number of Positions	6
Number of Rows	1
Wire Entry Angle	180°

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------

Body Features

Primary Product Color	Green
Product Orientation	Vertical



Contact Features

Contact Mating Area Plating Material	Tin
Contact Base Material	Copper
Contact Current Rating (Max)	6 A

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Method to Wire & Cable	Push-in

Housing Features

Housing Material	High Temperature Nylon or Polyester
------------------	-------------------------------------

Dimensions

Wire Size	26 - 20 AWG
-----------	-------------

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Method	Box & Carton
------------------	--------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-B8519-P7565
Poke-In Connector, BUCHANAN WireMate

TE Part # CAT-SL36-M6642B
Miniature Headers, SlimSeal

TE Part # 2834334-2
4.0PITCH ITB CONN_2P_W CAP_NATURAL

TE Part # 2834167-3
RELEASABLE SLIM CONTACT

TE Part # 2834385-2
RELEASE POKE-IN CONNECTOR_2P_NATURAL

Customers Also Bought

TE Part # MS580302BA01-00
MS5803-02BA01 DIGIT PRESSURE SENSOR TUBE

TE Part # 409534-001
CES-1

TE Part # 1-2834015-4
4POS 2.54MM TES CONN.

TE Part # 3-2176391-1
RQ 1206 25K5 0.1% 10PPM 5K RL



TE Part # NB13982001
TAT-125-1/8-0-STK

TE Part # T4040034041-000
M8.MLE.PNLREAR.4POS.STR
PCBSHLD

TE Part # 917353-000
SGRP-2

TE Part # 750648-000
D-1744-03

TE Part # EDA202N00000501000
915 BULKHEAD CONNECTOR

TE Part # EKA201N00330500000
915 EXTENSION

Documents

Product Drawings
6POS 2.54MM TES CONN.

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_1-2834015-6_1.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1-2834015-6_1.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1-2834015-6_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages
Modular Screwless Terminal Blocks Flyer

English

Product Specifications
Application Specification

English

Instruction Sheets
Instruction Sheet (non U.S.)

1-2834015-6

PCB Terminal Blocks, Receptacle, Wire-to-Board, 6 Position, 1 Row, 180° Wire Entry Angle, 26 - 20 AWG Wire Size, Operating Voltage 300 VAC



English