




Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Flag**
UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Flag
Contact Mating Retention	With

Mechanical Attachment

Mating Alignment Type	Polarization
Mating Alignment	With



Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Housing Material	Nylon
------------------	-------

Dimensions

Product Length	22.9 mm[.901 in]
----------------	------------------

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1000
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 172763-1 250 PL MKII FLAG REC. 18-14AWG PTBR	 TE Part # 172765-1 PL 250 FLAG REC 14-12 0.40 X 49.2 PTBR	 TE Part # 172761-1 PL 250 FLAG REC 18-22 0.40 X 49.2 PTBR	 TE Part # 172763-2 PL MKII 250 REC 18-14AWG PRE-TIN NB109
 TE Part # 3-172076-1 POSITIVE LOCK 250 HOUSING RECEPTACLE	 TE Part # 368612-2 POSITIVE LOCK 250 TERMINAL-FLAG		

Also in the Series | Positive Lock 250

 Automotive Terminals(1)	 Crimp Terminal Housings(192)	 Insertion & Extraction Tools(3)	 Insulation Boots & Sleeves(4)
 Quick Disconnects(186)			

Customers Also Bought



TE Part # 3-644038-4
04P MTA100 CONN ASSY POL 15AU

TE Part # 1-746610-4
16 DIP PLUG, 100CL, LEAD FREE

TE Part # 52265
TERMINAL R PG 6 10

TE Part # 770006-3
UMN II SOK PTPPHBZ

TE Part # 3-794013-1
MINI AMP-IN 12 AWG WIRE

TE Part # 63816-1
TAB, MAG-MATE 250F TPBR

TE Part # 63459-3
MAG-MATE 250 F-TAB 15-16 TPBR

TE Part # 3-641190-4
04P MTA100 CONN ASSY RED LF

TE Part # 1-172469-2
PL 250 (6.3 MM) HOUSING BLUE 6/6
NYLON

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-172469-1_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-172469-1_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-172469-1_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Positive Lock Receptacles

English

POS_LOCK_MII_QRG

English



Product Specifications

250 Series, Flag Positive Lock MK II Connector

Japanese

Product Specification

Japanese

Instruction Sheets

AMP* "250" FLAG POSITIVE LOCK CONNECTOR

English

Instruction Sheet (non U.S.)

English

Agency Approvals

UL Report

English