




Connectors > Connector Accessories > Connector Hardware



Hardware Accessory Function: **Coding & Keying**

Connector Hardware Accessory Type: **Keying Plug**

Operating Temperature (Max): **105 °C [ 221 °F ]**

Operating Temperature Range: **-55 – 105 °C [ -67 – 221 °F ]**

Features

Product Type Features

Hardware Accessory Function	Coding & Keying
Connector Hardware Accessory Type	Keying Plug

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1-1827863-6  
DYNAMIC 1100D REC HSG X 32P  
BLACK

Also in the Series | Dynamic 1000 Series

Connector Contacts(40)

Connector Hardware(3)

Insertion & Extraction Tools(2)

PCB Headers & Receptacles(173)

Rectangular Connector Housings(2)

Standard Rectangular Connectors(4)

Wire-to-Board Connector Assemblies & Housings(159)

Customers Also Bought



TE Part #1-1903131-3  
Receptacle and Tab Housing: 2.5 mm Pitch, 250V

TE Part #1903117-2  
DYNAMIC D1000 TAB CONT AU 0.38 um L L/P

TE Part #1-2040516-5  
DYNAMIC 1100D HDR ASSY V 10PX BLACK GOLD

TE Part #2013285-2  
DYNAMIC D-5 DYNATAP 20P ASSY P /M BOTTOM

TE Part #1-2040444-3  
DYNAMIC 1500T TAB HSG 9PX F/H

TE Part #2229983-1  
D1200-RITS RELAY BOARD ASSY 10 POSITION

Documents

Product Drawings

DYNAMIC D-1000 KEYING PLUG

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1939588-1\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1939588-1\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1939588-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.