



## DCDK16-8-8-A

Ruland DCDK16-8-8-A, 1/2" x 1/2" Double Disc Coupling, Aluminum, Clamp Style With Keyway, 1.000" OD, 1.374" Length



### Description

Ruland DCDK16-8-8-A is a clamp double disc coupling with 0.5000" x 0.5000" bores, 1.000" OD, 1.374" length, and 1/8" x 1/8" keyways. It is zero-backlash and has a balanced design for reduced vibration at high speeds. The double disc design is comprised of two anodized aluminum hubs, two sets of thin stainless steel disc springs, and a center spacer allowing each disc to bend individually and accommodate all types of misalignment. DCDK16-8-8-A is lightweight and has low inertia making it well suited for applications with speeds up to 10,000 RPM. Hardware is metric and tests beyond DIN 912 12.9 standards for maximum torque capabilities. Ruland manufactures DCDK16-8-8-A to be torsionally rigid and an excellent fit for precise positioning stepper servo applications commonly found in semiconductor, solar, printing, machine tool, and test and measurement systems. It is machined from solid bar stock that is sourced exclusively from North American mills and RoHS3 and REACH compliant. DCDK16-8-8-A is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

### Product Specifications

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                     |                                                                                             |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Bore (B1)</b>                      | 0.5000 in                                                                                                                                                                                                                                                                                                                                                                                                                                           | <b>Small Bore (B2)</b>              | 0.5000 in                                                                                   |
| <b>Keyway (K1)</b>                    | 1/8 in                                                                                                                                                                                                                                                                                                                                                                                                                                              | <b>Keyway (K2)</b>                  | 1/8 in                                                                                      |
| <b>B1 Max Shaft Penetration</b>       | 0.467 in                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>B2 Max Shaft Penetration</b>     | 0.467 in                                                                                    |
| <b>Outer Diameter (OD)</b>            | 1.000 in                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>Bore Tolerance</b>               | +0.001 in / -0.000 in                                                                       |
| <b>Length (L)</b>                     | 1.374 in                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>Hub Width (LH)</b>               | 0.467 in                                                                                    |
| <b>Recommended Shaft Tolerance</b>    | +0.0000 in / -0.0005 in                                                                                                                                                                                                                                                                                                                                                                                                                             | <b>Forged Clamp Screw</b>           | M3                                                                                          |
| <b>Screw Material</b>                 | Alloy Steel                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>Hex Wrench Size</b>              | 2.5 mm                                                                                      |
| <b>Screw Finish</b>                   | Black Oxide                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>Seating Torque</b>               | 2.1 Nm                                                                                      |
| <b>Number of Screws</b>               | 2 ea                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Dynamic Torque Reversing</b>     | 12.5 lb-in                                                                                  |
| <b>Angular Misalignment</b>           | 2.0°                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Dynamic Torque Non-Reversing</b> | 25 lb-in                                                                                    |
| <b>Parallel Misalignment</b>          | 0.006 in                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>Static Torque</b>                | 50 lb-in                                                                                    |
| <b>Axial Motion</b>                   | 0.012 in                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>Torsional Stiffness</b>          | 61 lb-in/Deg                                                                                |
| <b>Moment of Inertia</b>              | 0.0111 lb-in <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                           | <b>Maximum Speed</b>                | 10,000 RPM                                                                                  |
| <b>Zero-Backlash?</b>                 | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Balanced Design</b>              | Yes                                                                                         |
| <b>Torque Wrench</b>                  | <a href="#">TW:BT-1R-1/4-18.3</a>                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>Recommended Hex Key</b>          | <a href="#">Metric Hex Keys</a>                                                             |
| <b>Full Bearing Support Required?</b> | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Material Specification</b>       | Hubs and Center Spacer:<br>2024-T351 Aluminum Bar<br>Disc Springs: Type 302 Stainless Steel |
| <b>Temperature</b>                    | -40°F to 200°F (-40°C to 93°C)                                                                                                                                                                                                                                                                                                                                                                                                                      | <b>Finish Specification</b>         | Sulfuric Anodized MIL-A-8625 Type II, Class 2 and ASTM B580 Type B Black Anodize            |
| <b>Manufacturer</b>                   | Ruland Manufacturing                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Country of Origin</b>            | USA                                                                                         |
| <b>Weight (lbs)</b>                   | 0.071300                                                                                                                                                                                                                                                                                                                                                                                                                                            | <b>UPC</b>                          | 634529173589                                                                                |
| <b>Tariff Code</b>                    | 8483.60.8000                                                                                                                                                                                                                                                                                                                                                                                                                                        | <b>UNSPC</b>                        | 31163008                                                                                    |
| <b>Note 1</b>                         | Stainless steel hubs are available upon request.                                                                                                                                                                                                                                                                                                                                                                                                    |                                     |                                                                                             |
| <b>Note 2</b>                         | Torque ratings are at maximum misalignment.                                                                                                                                                                                                                                                                                                                                                                                                         |                                     |                                                                                             |
| <b>Note 3</b>                         | Performance ratings are for guidance only. The user must determine suitability for a particular application.                                                                                                                                                                                                                                                                                                                                        |                                     |                                                                                             |
| <b>Note 4</b>                         | Torque ratings for the couplings are based on the physical limitations/failure point of the disc springs. Under normal/typical conditions the hubs are capable of holding up to the rated torque of the disc springs. In some cases, especially when the smallest standard bores are used or where shafts are undersized, slippage on the shaft is possible below the rated torque of the disc springs. Keyways are available to provide additional |                                     |                                                                                             |

torque capacity in the shaft/hub connection when required. Please consult technical support for more assistance.

---

**Prop 65**

 **WARNING** This product can expose you to chemicals including Ethylene Thiourea and Nickel (metallic), known to the State of California to cause cancer, and Ethylene Thiourea known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

**Installation Instructions**

1. Align the bores of the DCDK16-8-8-A double disc coupling on the shafts that are to be joined and determine if the misalignment parameters are within the limits of the coupling. (*Angular Misalignment: 2.0°, Parallel Misalignment: 0.006 in, Axial Motion: 0.012 in*)
  2. Fully tighten the M3 screw on the first hub to the recommended seating torque of 2.1 Nm using a 2.5 mm hex torque wrench.
  3. Before tightening the screw on the second hub, rotate the coupling by hand to allow it to reach its free length.
  4. Tighten the screw on the second hub to the recommended seating torque. Make sure the coupling remains axially relaxed and the misalignment angle remains centered along the length of the coupling.
  5. The shafts may extend into the relieved portion of the bore as long as it does not exceed the shaft penetration length of 0.467 in.
-