

Part Number : 2077820603

Series Number : 207782

Product Category : Connector Housings

Product Description : Squaba 3.6 Sealed Receptacle Assembly, 3.60mm Pitch, 3 Circuits, Single Row, Glow-Wire Capable, Key F, Orange, UL1007/UL1061 Compatible

Status : Active

Documents & Resources

Drawings

Drawing 2077820603_sd.pdf

Packaging Design Drawing 2077820000-PK-000.pdf

3D Models and Design Files

3D Model 2077820603_stp.zip

Specifications

Application Specification 2077760000-AS-000.pdf

Product Specification 2077760000-PS-000.pdf

Test Summary 2077760000-TS-000.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|--|
| Status | Active |
| Category | Connector Housings |
| Series | 207782 |
| Description | Squba 3.6 Sealed Receptacle Assembly, 3.60mm Pitch, 3 Circuits, Single Row, Glow-Wire Capable, Key F, Orange, UL1007/UL1061 Compatible |
| Application | Power, Signal, Wire-to-Wire |
| Product Family | Squba Sealed Wire-to-Wire Connectors |
| Product Name | Squba |
| UPC | 196823172144 |

Agency

| | |
|----|--------|
| UL | E29179 |
|----|--------|

Physical

| | |
|-----------------------|------------|
| Circuits (maximum) | 3 |
| Color - Resin | Orange |
| Flammability | 94V-0 |
| Gender | Receptacle |
| Glow-Wire Capable | Yes |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Resin | Nylon |
| Net Weight | 4.042/g |
| Number of Rows | 1 |
| Packaging Type | Tray |

| | |
|-------------------------------|----------------|
| Panel Mount | No |
| Pitch - Mating Interface | 3.60mm |
| Pitch - Termination Interface | 3.60mm |
| Polarized to Mating Part | Yes |
| Temperature Range - Operating | -40° to +105°C |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|-------------|---------------|
| | <u>207778</u> |

Use with Part(s)

| Description | Part Number |
|--------------------------------|---------------|
| Squba 3.6 Receptacle Terminals | <u>207777</u> |

This document was generated on May 28, 2024