




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 - .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.3 mm [.012 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.3 mm[.012 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--	--



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Product Length	16.13 mm[.635 in]
Compatible Insulation Diameter Range	1.52 - 2.54 mm[.06 - .1 in]
Wire Size	.32 - .82 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	15000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # 2063846-1 CCII 110 FASTON REC 24-18 ASSY	TE Part # 2150049-1 OCEAN-2.0-APPLICATOR-E-062F090F-REM	TE Part # 2150049-2 OCEAN-2.0-APPLICATOR-E-062F090F-REA	TE Part # 2150636-1 OCEAN-2.0-APPLICATOR-E-062F090OV-REM
TE Part # 2150636-2 OCEAN-2.0-APPLICATOR-S-062F090OVA	TE Part # 7-2150049-7 OCEAN_2.0_SPARE_PART_KIT-062F090F	TE Part # 7-2150636-7 OCEAN_2.0_SPARE_PART_KIT-062F090OV	TE Part # 7-2150049-2 OCEAN-2.0-APPLICATOR-E-062F090FA
TE Part # 7-2150636-1 OCEAN-2.0-APPLICATOR-S-062F090OV	TE Part # 7-2150636-2 OCEAN-2.0-APPLICATOR-S-062F090OVA		

Also in the Series | FASTON 110

Crimp Terminal Housings(13)	Insertion & Extraction Tools(1)	PCB Terminals(22)	Quick Disconnects(169)

Customers Also Bought



 TE Part # 1-1375820-2 Receptacle Housing: 2.54mm, 1 Row, CST-100 II	 TE Part # 208716-1 CMC PLUG ASSEMBLY,SZ 14	 TE Part # 350570-2 UMNL SOK 24-18 AUBR	 TE Part # 2-521102-2 ULTRA-FAST 187 ASY Tab 22-18 TPBR
 TE Part # 3-520150-2 ULTRA-FAST 187 ASY REC 16-14 AWG TPBR	 TE Part # 1375819-3 CST-100 II CONTACT 30 GOLD PLT	 TE Part # 5-103945-7 2X8 MTE SHRD PIN SR LATCH .100	 TE Part # 641994-1 MTA100 KEYING PLUG W/CARRIER

Documents

Product Drawings

110 FASTON REC 22-18 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_60415-1_S.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_60415-1_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_60415-1_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

60415-1

Quick Disconnects, Receptacle, 22 - 18 AWG Wire Size, .32 - .82 mm² Wire Size,
Mating Tab Width 2.8 mm [.11 in], Straight, Brass, FASTON 110



English