




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 - 1.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	18.8 mm[.74 in]
Compatible Insulation Diameter Range	1.52 - 2.8 mm[.06 - .11 in]
Wire Size	.51 - 1.31 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 936663-1
PL 187 REC 20-16 AWG 0.3 X 14.0
PTPBR

TE Part # 7-2150184-2
OCEAN_2.0_Applicator-E-090F140FA

Also in the Series | Mark II

Automotive Connector Locks & Position Assurance(1)

Automotive Housings(21)

Automotive Terminals(18)

Connector Seals & Cavity Plugs(1)

Crimp Terminal Housings(76)

Insertion & Extraction Tools(2)

Other Automotive Connector Accessories(4)

Quick Disconnects(57)

Also in the Series | Positive Lock 187

Crimp Terminal Housings(86)

Insertion & Extraction Tools(2)

Insulation Boots & Sleeves(7)

Quick Disconnects(57)

Customers Also Bought



TE Part # 3-641126-4
04P MTA100 HDR ASY FL/STR LF

TE Part # 63969-1
FASTON 205/250 PCB MOUNTED TPBR

TE Part # 350415-1
.093 COMM P&S SOK 14-20 PTPBR

TE Part # 175164-1
250 PL EX REC. 18-14AWG ST

TE Part # 6-160430-6
187 FASTON REC 20-16 AWG BR

TE Part # 1827387-1
GIC 3.3 PLUG HOUSING 8P

TE Part # 179463-4
AMP POWER DBL LOCK HSG 2P

TE Part # 1955415-1
3P CLUSTER BLOCK HOUSING

TE Part # 2238190-1
LOW PROFILE MINI AMP-IN SM

TE Part # 1-2186322-1
T200-IDENT-TRANSPORT-MODULE

Documents

Product Drawings

PL 187 TERMINAL REC 20-16 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_63498-1_M.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63498-1_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63498-1_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



Positive Lock Receptacles

English

POS_LOCK_MIL_QRG

English

Product Specifications

Application Specification

English