



Connectors > Contacts > Connector Contacts



Contact Type: **Pin**
Contact Mating Area Plating Material: **Gold**
Wire Contact Termination Area Plating Material: **Nickel**
Operating Voltage: **250 VAC**
Contact Retention Within Housing: **With**

Features

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Contact Features

Contact Fabrication	Stamped & Formed
Mating Pin Diameter	1.57 mm[.062 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Wire Contact Termination Area Plating Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Type	Pin
Contact Mating Area Plating Material	Gold
Wire Contact Termination Area Plating Material	Nickel
Contact Retention Within Housing	With
Contact Base Material	Brass



Contact Current Rating (Max)	9 A
------------------------------	-----

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	Without
Contact Retention Type Within Housing	Locking Lance

Dimensions

Compatible Insulation Diameter Range	1.27 - 2.79 mm[.05 - .11 in]
Wire Size	.2 - .82 mm ²

Usage Conditions

Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	6000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





 TE Part # 2063388-1 TOOL, EXTRACTION	 TE Part # 770278-1 01P .062 COMM P&S PLUG	 TE Part # 770334-1 04P .062 COMM P&S PLUG	 TE Part # 770277-1 01P .062 COMM P&S RECPT
 TE Part # 770335-1 04P .062 COMM P&S RECPT	 TE Part # 770071-1 03P .093 COMM P&S RECPT HSG	 TE Part # 770333-1 03P .062 COMM P&S RECPT	 TE Part # 770340-1 02P .062 COMM P&S PLUG
 TE Part # 770343-1 02P .062 COMM P&S RECPT	 TE Part # 770331-1 03P .062 COMM P&S PLUG	 TE Part # 770342-1 02P .062 COMM P&S RECPT	 TE Part # 770274-1 04P .062 COMM P&S RECPT





 TE Part # 770275-1 04P .062 COMM P&S PLUG	 TE Part # 770341-1 02P .062 COMM P&S PLUG	 TE Part # 770355-1 06P .062 COMM P&S PLUG	 TE Part # 770356-1 06P .062 COMM P&S RECPT
 TE Part # 770419-1 02P .062 COMM P&S RECPT	 TE Part # 770428-1 09P .062 COMM P&S PLUG	 TE Part # 770429-1 09P .062 COMM P&S RECEPT	 TE Part # 770433-1 04P .062 COMM P&S PLUG

Also in the Series

Commercial Pin and Socket Connectors

 Connector Contacts(41)	 Insertion & Extraction Tools(3)	 Rectangular Connector Housings(10)	 Rectangular Power Connectors(84)
 Standard Rectangular Connectors(1)			

Customers Also Bought

 TE Part # 1-776163-5 AMPSEAL PCB Right-Angle Headers	 TE Part # 770340-1 02P .062 COMM P&S PLUG	 TE Part # 63475-2 187 FASTON REC 20-16 AWG TPBR	 TE Part # 770433-1 04P .062 COMM P&S PLUG
---	---	--	--



TE Part # 7-1879337-3
CPF 0603 14K 1% 50PPM 1K RL

TE Part # 1676240-2
RN 0805 1K69 0.1% 10PPM 1KRL

TE Part # 2-1474654-6
FSN-24A-15

TE Part # 354508-1
PLATE, INDEXING

Documents

Product Drawings

[.062 COMM P&S PIN AUNI/BR](#)

English

CAD Files

[3D PDF](#)

English

Customer View Model

[ENG_CVM_350629-5_U.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_350629-5_U.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_350629-5_U.3d_stp.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_350629-5_AT.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_350629-5_AT.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_350629-5_AT.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

English

Product Specifications

[Application Specification](#)

English

350629-5

Pin Contact, Gold, 250 VAC, Locking Lance Contact Retention, 24 - 18 AWG Wire Size, .2 - .82 mm² Wire Size, Commercial Pin and Socket Connectors

