




Terminals & Splices > Quick Disconnects > ULTRA POD: Flag, Receptacle Assembly, Tin Plated, .250 inch



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 - .82 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

[All ULTRA POD: Flag, Receptacle Assembly, Tin Plated, .250 inch \(9\)](#)

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Tin



Crimp Type	Tab-Lok
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	23.03 mm[.905 in]
Compatible Insulation Diameter Range	1.27 - 2.54 mm[.05 - .1 in]
Wire Size	.32 - .82 mm²

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	-40 - 150 °C[-40 - 302 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1800
Packaging Method	Strip/Reel

Other

Barrel Color	Natural
--------------	---------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # CAT-UL8-25021
ULTRA POD: Flag, Receptacle Assembly, Tin Plated, .250 inch



TE Part # 520971-1
ULTRA-POD 250 ASY REC 18-14 AWG BR




TE Part # 521411-1
ULTRA-POD 250 ASY REC 22-18 AWG BR



TE Part # 521282-1
ULTRA-POD 250 ASS REC 18-14 AWG BR LIF



TE Part # 680020-1
MACH,U-POD FLAG9EAPR080F1400 T



TE Part # 680020-2
MACH,U-PODFLAG 9EAPR080F1400 K

Also in the Series | Ultra-Pod 250



Insertion & Extraction Tools(2)



Quick Disconnects(43)



Customers Also Bought



TE Part # 61352-1
RING .197 (5.0 MM) 10-6 AWG TPBR



TE Part # 63476-2
187 FASTON FLAG REC 20-16 AWG TPBR




TE Part # 61795-3
RING 18-14 AWG TPBR



TE Part # 521600-2
ULTRA POD: Flag, Receptacle Assembly, Tin Plated, .187 inch



TE Part # 794742-1
12P UMNL PLUG HSG NATL



TE Part # 63526-1
FLANGED SPADE TERMINAL 12-10 AWG BR



TE Part # 1-1969789-3
POSI-LOK MKIII, 7MM SILO POW CORD,2P,RED



TE Part # 1969458-3
POSI-LOK MKIII,7MM SILO POW CORD,2P,BLUE



TE Part # 2238212-2
RECEPTACLE, POSITIVE-LOCK, RAST 6.35

Documents

Product Drawings
ULTRA-POD 250 ASY REC 22-18 AWG TPBR
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_521411-2_E.2d_dxf.zip
English
Customer View Model
ENG_CVM_CVM_521411-2_E.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_521411-2_E.3d_stp.zip
English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



Datasheets & Catalog Pages

Ultra-Fast and Ultra Fast Plus

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English