



AMP

TE Internal #: 1-66359-9
Pin Contact, Tin, 18 - 14 AWG Wire Size, .8 - 2 mm² Wire Size,
Crimp, Copper Nickel Alloy, Power & Signal, -67 - 194 °F [-55 - 90 °
C]
[View on TE.com >](#)

Connectors > Contacts > Connector Contacts



Contact Type: **Pin**
Contact Mating Area Plating Material: **Tin**
Wire Contact Termination Area Plating Material: **Tin**
Contact Retention Within Housing: **With**
Wire Size: **18 - 14 AWG**

Features

Contact Features

Mating Pin Diameter	1.57 mm[.062 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Wire Contact Termination Area Plating Thickness	2.54 µm[100 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Thickness	2.54 µm[100 µin]
Contact Mating Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Type	Pin
Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With
Contact Base Material	Copper Nickel Alloy
Contact Current Rating (Max)	25 A



Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Compatible Insulation Diameter Range	2.03 - 2.54 mm[.08 - .1 in]
Wire Size	.8 - 2 mm²

Usage Conditions

Operating Temperature Range	-55 - 90 °C[-67 - 194 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Method	Reel
------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # CAT-AM71-C83998C Circular Plastic Connector, CMC Series 1	 TE Part # CAT-AM71-C83998Y One-Piece Connector, Sealed, CPC Series 1	 TE Part # CAT-AM71-C83998J Cable/Panel Mount Connector, CPC Series 1	 TE Part # CAT-AM71-C83998K Circular Connector, Environmentally Sealed, CPC Series 6
 TE Part # 91519-1 CCII TYPE III+ PIN SKT 18-14 ASSY	 TE Part # 200893-2 INSERTION TOOL CONT	 TE Part # 539972-1 EXTRACTION TOOL	 TE Part # 305183 EXTRACT TOOL TYPE 2 20-16
 TE Part # 2151101-1 OCEAN_2.0_APPLICATOR-S-090F120O-RSM	 TE Part # 2151101-2 OCEAN_2.0_APPLICATOR-S-090F120O-RSA	 TE Part # 5-2151101-1 OCEAN_2.0_APPLICATOR-S-090F120O-RSM	 TE Part # 5-2151101-2 OCEAN_2.0_APPLICATOR-S-090F120O-RSA
 TE Part # 7-2151101-7 OCEAN_2.0_SPARE_PART_KIT-090F120O	 TE Part # 7-2151101-2 OCEAN_2.0_APPLICATOR-S-090F120O		

Customers Also Bought



TE Part # 208714-1
CMC PLUG ASSEMBLY,SZ 14-7

TE Part # 208945-5
SZ 14 UNASSM KIT,CMC

TE Part # 208209-2
METRIMATE PIN HSG 19 POSN

TE Part # 208210-2
METRIMATE SOCKET 19 POSN

TE Part # 160759-3
250 PL MKI REC. 20-15AWG TPBR

TE Part # 1-643067-5
15P MTA156 MOLDED COVER

TE Part # 9-227260-0
LOCKWASHER,TERMINAL,LEAD FREE

TE Part # 329331
T-SHIELD,.033-.059

Documents

Product Drawings

III+PIN,18-14,TIN,STRIP

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-66359-9_AG.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-66359-9_AG.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-66359-9_AG.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

Signal Contacts

English

Product Specifications

Product Specification

English

1-66359-9

Pin Contact, Tin, 18 - 14 AWG Wire Size, .8 - 2 mm² Wire Size, Crimp, Copper Nickel Alloy, Power & Signal, -67 - 194 °F [-55 - 90 °C]

