




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 - .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Product Length	17.9 mm[.705 in]
Compatible Insulation Diameter Range	2.29 - 3.3 mm[.09 - .13 in]
Wire Size	.32 - .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	15000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150560-1
OCEAN-2.0-APPLICATOR-E-062F140F-REM

TE Part # 2150560-2
OCEAN-2.0-APPLICATOR-E-062F140F

TE Part # 7-2150560-7
OCEAN_2.0_SPARE_PART_KIT-062F140F

TE Part # 7-2150560-1
OCEAN-2.0-APPLICATOR-E-062F140F

TE Part # 7-2150560-2
OCEAN-2.0-APPLICATOR-E-062F140FA

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(22)

Quick Disconnects(169)

Customers Also Bought





TE Part # 1-1355200-1
MCP2,8BU-GEH ASSY2P



TE Part # 1456985-3
1X6 Fem unsealed low profile assy Key C




TE Part # 62138-1
187 FASTON REC 24-20 TPBR



TE Part # 1742785-1
110 FASTON,REC.,22-18 AWG,PTBR



TE Part # 485043-1
SPLICE 4000-9000 .020 BR



TE Part # 62307-2
AMVAR SPLC 1500-5000 016TPBR




TE Part # 8-1971775-3
PTL 2X3 CAP PANEL MT HIGH TEMP KEY D NAT



TE Part # NB17982001
RNF-100-1-1/2-CL-STK



TE Part # 1811495-6
Assembly, 6 Position Terminal



TE Part # 5-2119582-2
CRIMPER, INSULATION F PREMIUM

Documents

Product Drawings
110 FASTON REC 22-18 AWG TPBR
English

CAD Files
Customer View Model
ENG_CVM_CVM_62094-1_V.2d_dxf.zip
English
3D PDF
3D
Customer View Model
ENG_CVM_CVM_62094-1_V.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_62094-1_V.3d_stp.zip
English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English