




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 - .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------



Dimensions

Terminal Material Thickness	.4 mm[.015 in]
Product Length	13.2 mm[.52 in]
Compatible Insulation Diameter Range	3 mm[.118 in]
Wire Size	.32 - .82 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Other

Line	FASTON .110
------	-------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part






numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 63138-1 110 FASTON REC 22-18 AWG TPBR	 TE Part # 42475-4 250 FASTON TAB 22-18 AWG TPBR	 TE Part # 61281-3 250 FASTON TAB 14-12 AWG TPBR	 TE Part # 63165-2 FASTON 110 AMPLIVAR TAB 23-19 MAG TPBR
 TE Part # 63932-1 110 FASTON TAB 22-18 AWG TPBR	 TE Part # 1494210-2 110 FASTON,TAB,22-17 AWG, JIS C260	 TE Part # 1742753-1 FASTON 2MM TAB 18-22AWG TPBR	 TE Part # 42490-4 187 FASTON TAB 22-18 AWG BR
 TE Part # 42475-2 250 FASTON TAB 22-18 AWG TPBR	 TE Part # 42474-3 250 FASTON TAB 18-14 AWG BR	 TE Part # 42475-3 250 FASTON TAB 22-18 AWG BR	 TE Part # 4151105-1 OCEAN-2.0-APPLICATOR-S-080F136F-RSM
 TE Part # 4151105-2 OCEAN-2.0-APPLICATOR-S-080F136F-RSA	 TE Part # 63535-1 TAB SPECIAL 025TPBR	 TE Part # 7-4151105-7 OCEAN_2.0_SPARE_PART_KIT-080F136F	 TE Part # 7-4151105-1 OCEAN-2.0-APPLICATOR-S-080F136F



Also in the Series | FASTON 110



Customers Also Bought



Documents

Product Drawings

110 FASTON,TAB,22-17 AWG, JIS C260

English

CAD Files

3D PDF

3D



Customer View Model

[ENG_CVM_CVM_1494210-1_B.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1494210-1_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1494210-1_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Agency Approvals

[Agency Approval Document](#)

English