




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.03 - 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	.32 mm
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.33 mm[.013 in]
Product Length	19.2 mm[.755 in]
Compatible Insulation Diameter Range	3.43 - 5.08 mm[.135 - .2 in]
Wire Size	1.03 - 2.62 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>






EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-1579007-4 EXTRACTION TOOL	 TE Part # 4-1579007-3 EXTRACTION TOOL KIT	 TE Part # 1989880-1 .250 SRS FASTIN-ON REC.	 TE Part # 626328-2 FF 250 RECEPTACLE 4.0-6.0 MM2 TPBR
 TE Part # 160950-1 FF 250 REC BR SOLDERING	 TE Part # 2150314-1 OCEAN_2.0_Applicator-E-110F180F- REM	 TE Part # 2150314-2 OCEAN_2.0_Applicator-E-110F180F- REA	 TE Part # 2150427-1 OCEAN_2.0_APPLICATION-E- 110F140OV-REM
 TE Part # 2150427-2 OCEAN_2.0_APPLICATION-E- 110F140OV-REA	 TE Part # 626096-2 .250 S FASTIN ON	 TE Part # 626328-1 FF 250 RECEPTACLE 4.0-6.0 MM2 BR	 TE Part # 7-2150314-7 OCEAN_2.0_SPARE_PART_KIT- 110F180F
 TE Part # 7-2150427-7 OCEAN_2.0_SPARE_PART_KIT- 110F140OV	 TE Part # 7-2150314-1 OCEAN_2.0_Applicator-E-110F180F	 TE Part # 7-2150314-2 OCEAN_2.0_Applicator-E-110F180F	 TE Part # 7-2150427-1 OCEAN_2.0_APPLICATION-E- 110F140OV



TE Part # 7-2150427-2
OCEAN_2.0_APPLICATOR-E-110F140OV

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(211)

Insertion & Extraction Tools(2)

PCB Terminals(2)

Quick Disconnects(254)

Customers Also Bought

TE Part # 160450-2
FF 250 TAB 18-14AWG TPPB

TE Part # 928962-4
FF 250 TAB 17-13 AWG .016 TPBR

TE Part # 42460-1
FF 250 TAB 18-14AWG BR

TE Part # 925712-1
.140 DIA SOCKET

TE Part # 1676291-2
RN 0805 2K55 0.1% 10PPM 1KRL

TE Part # HD34-24-21PN-072
REC, 21P, AL, N, THD ADPT DRAIN, 12 /16,P

TE Part # 215598-1
4P.CI-2 PIN HSG.

TE Part # 2-2176246-5
CRGS2512 5% 100R

TE Part # 365057-1
2P TAB HSG NAT



Documents

Product Drawings

FF 250 REC 1.0-2.5MM2 TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-160448-5_AR_c-6-160448-5-ar.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-160448-5_AR_c-6-160448-5-ar.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-160448-5_AR_c-6-160448-5-ar.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

EB**General Application Specification for Open Barrel Terminals

English

Application Specification

English