

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	2	RE - F - 08696	S.K	R.T	03.03.12	△	△				
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE	-55°C TO 85°C			STORAGE TEMPERATURE RANGE	-10°C TO 50°C (PACKED CONDITION)					
	VOLTAGE	30V AC			OPERATING OR STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 90 % MAX (NOT DEWED)					
	CURRENT	0.3A			APPLICABLE CABLE	t=0.20±0.03mm, GOLD PLATING					
SPECIFICATIONS											
ITEM	TEST METHOD				REQUIREMENTS				QT	AT	
CONSTRUCTION											
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				×	×	
MARKING	CONFIRMED VISUALLY.								×	×	
ELECTRIC CHARACTERISTICS											
CONTACT RESISTANCE	AC 20mV MAX., 1mA.				100mΩ MAX. INCLUDING FPC BULK RESISTANCE (L=12mm, THICKNESS OF COPPER FOIL: 35 μm)				×	×	
INSULATION RESISTANCE	100V DC.				50 MΩ MIN.				×	×	
VOLTAGE PROOF	90V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×	×	
MECHANICAL CHARACTERISTICS											
FPC INSERTION FORCE	MEASURED BY APPLICABLE FPC. (THICKNESS OF FPC SHALL BE t=0.20mm AT INITIAL CONDITION.)				0.15N/PIN MAX. (CONNECTOR, FPC AT INITIAL CONDITION)				×	—	
FPC RETENTION FORCE	MEASURED BY APPLICABLE FPC. (THICKNESS OF FPC SHALL BE t=0.20mm AT INITIAL CONDITION.)				0.30N/PIN MIN. (CONNECTOR, FPC AT INITIAL CONDITION)				×	—	
MECHANICAL OPERATION	10 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—	
VIBRATION	FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75mm, — m/s ² FOR 10 CYCLES IN 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② CONTACT RESISTANCE: 100 mΩ MAX.				×	—	
SHOCK	981m/s ² , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 DIRECTIONS.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—	
ENVIRONMENTAL CHARACTERISTICS											
DAMP HEAT (STEADY STATE)	EXPOSED AT -40 °C, RELATIVE HUMIDITY 90 TO 95%, 96h.				① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—	
DAMP HEAT,CYCLIC	EXPOSED AT -10 TO +65°C, RELATIVE HUMIDITY 90 TO 96%, 10 CYCLES, TOTAL 240 h.				① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—	
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
					S.OKAMURA	S.OKAMURA	R.TAKAYASU	M.ISHIDA			
02.11.11					02.11.11	02.11.11	02.11.12				
Unless otherwise specified, refer to JIS C 5402.											
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test											
 HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET			PART NO. FH23 - *S - 0.3SHAW(05)						
CODE NO.(OLD) CL		DRAWING NO. ELC4 - 153685 - 01			CODE NO. CL 586						
1 / 2											

SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS			QT	AT
RAPID CHANGE OF TEMPERATURE	TEMPERATURE-55→+15TO+35→+85→+15TO+35°C TIME 30→ 2~3 → 30→ 2~3 min. UNDER 5 CYCLES.	① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
DRY HEAT	EXPOSED AT 85 °C, 96 h.	① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
COLD	EXPOSED AT -55°C, 96 h.	② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
CORROSION SALT MIST	EXPOSED AT 35°C, 5% SALT WATER SPRAY FOR 96h.	① CONTACT RESISTANCE: 100 mΩ MAX.			X	—
HYDROGEN SULPHIDE [JIS C 0092]	EXPOSED AT 40°C, RELATIVE HUMIDITY 80%, 10 ~ 15 PPM FOR 96h.	② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
SURPHUR DIOXIDE [JIS C 0090]	EXPOSED AT 40 °C , RELATIVE HUMIDITY 80%, 25 PPM FOR 96 h.	③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.			X	—
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : PEAK TMP. 250°C MAX. REFLOW TMP. 230°C MIN FOR 60 sec. 2) SOLDERING IRONS : TMP. 350±5°C FOR 5 sec.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			X	—
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 235°C FOR IMMERSION DURATION, 2 sec.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.			X	—
REMARKS						
Unless otherwise specified, refer to JIS C 5402.		DRAWN S.OKAMURA 02.11.11	DESIGNED S.OKAMURA 02.11.11	CHECKED R.TAKAYASU 02.11.11	APPROVED M.ISHIDA 02.11.12	RELEASED
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test						
 HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO. FH23 - *S - 0.3SHAW(05)		
CODE NO.(OLD)	DRAWING NO.	CODE NO.		CL 586		
CL	ELC4 - 153685 - 01					