

SCHRACK

TE Internal #: 1393845-5

Power Relays, Standard, Monostable, 500 mW Coil Power Rating
DC, 1100 Ω Coil Resistance, 24 VDC Coil Voltage, 2 Form C (CO),
8A Contact Current Rating

[View on TE.com >](#)

Relays & Contactors > Relays > Power Relays

Relay Type: **Standard**Coil Magnetic System: **Monostable**Coil Power Rating DC: **500 mW**Coil Resistance: **1100 Ω**Coil Voltage Rating: **24 VDC**

Features

Product Type Features

Relay Type	Standard
------------	----------

Configuration Features

Contact Arrangement	2 Form C (CO)
---------------------	---------------

Contact Number of Poles	2
-------------------------	---

Electrical Characteristics

Coil Current	.024 A
--------------	--------

Insulation Initial Dielectric Between Open Contacts	1000 Vrms
-----------------------------------------------------	-----------

Coil Power Rating	.5 W
-------------------	------

Contact Limiting Continuous Current	8 A
-------------------------------------	-----

Insulation Initial Dielectric Between Adjacent Contacts	2500 Vrms
---------------------------------------------------------	-----------

Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
-------------------------------------------------------	-----------

Coil Power Rating DC	500 mW
----------------------	--------

Coil Resistance	1100 Ω
-----------------	--------

Coil Voltage Rating	24 VDC
---------------------	--------

Contact Current Rating	8 A
------------------------	-----

Contact Switching Voltage (Max)	400 VAC
---------------------------------	---------

Contact Voltage Rating	250 VAC
------------------------	---------

Body Features

Product Weight	18 g [.635 oz]
----------------	----------------

Contact Features

Contact Plating Material	Silver-Nickel Gold Covered
Contact Material	AgNi0.15, Silver-Nickel Gold Covered

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins

Mechanical Attachment

Product Mount Type	Printed Circuit Board
--------------------	-----------------------

Dimensions

Insulation Clearance Between Contact & Coil	8 mm [.315 in]
Insulation Creepage Between Contact & Coil	8 mm [.315 in]
Product Width	12.6 mm [.496 in]
Product Length	29 mm [1.14 in]
Product Height	25.5 mm [1 in]

Usage Conditions

Environmental Ambient Temperature (Max)	70 °C [158 °F]
Operating Temperature Range	-45 - 70 °C [-40 - 158 °F]

Operation/Application

Actuating System	DC
Solder Process	Wave Solder
Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Box & Tube
------------------	------------

Other

Length Class (Mechanical)	25 - 30 mm
Insulation Initial Dielectric Between Coil & Contact Class	4000 V
Environmental Ambient Temperature Class	-40 - 70 °C
Insulation Creepage Class	8 mm
Insulation Clearance Class	8 mm
Height Class (Mechanical)	25 - 30 mm
Coil Power Rating Class	500 - 600 mW

Width Class (Mechanical)	12 - 16 mm
Contact Current Class	5 - 10 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6-trimethylphenyl)- (2% in Component Part) <small>Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.</small>
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

		
TE Part # 1-1393161-9 RP28500-RETAINING CLIP	TE Part # 1860996-1 RP16C01 PLASTIC RETAINING CLIP HIGH	TE Part # 1860991-1 RT78602, RELAY SOCKET PCB 5MM

Customers Also Bought



TE Part # 1-5499923-0
A/L UNIV HDR 50P VERT LG LAT



TE Part # 1461492-2
OJT-SS-105LM,000



TE Part # 1-1393230-1
RP3SL024



TE Part # 167301-4
MOD-4 REC.CONT.SCP



TE Part # 2176416-4
9W STD M/OX 5% 68R



TE Part # 294285-E
DRCB 0,80 26 M SMD * 137 E009 196
GURT *



TE Part # 1337775-3
75 OHM COAX BNC STR PLUG-P99-E



TE Part # 838103-E
IDCCS SMC 1,27 12 * AU AUI 1500 PVC

Documents

CAD Files

[3D PDF](#)

[3D](#)

[Customer View Model](#)

[ENG_CVM_CVM_1393845-5_A.2d_dxf.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_1393845-5_A.3d_igs.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_1393845-5_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[PCB Accessories Industrial Power Relays](#)

English

[Power PCB Relay RPII/2](#)

English

Product Specifications

[Definitions General Purpose Relays](#)

English

Agency Approvals

[VDE Certificate](#)

English