




N-Channel Enhancement Mode Power MOSFET

Description The G33N03S uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications. General Features • V_{DS} • I_D (at $V_{GS} = 10V$) • $R_{DS(ON)}$ (at $V_{GS} = 10V$) • $R_{DS(ON)}$ (at $V_{GS} = 4.5V$) • 100% Avalanche Tested • RoHS Compliant 30V 13A < 12mΩ < 13mΩ Application • Power switch • DC/DC converters		 Schematic diagram  Marking and pin assignment  SOP-8	
Device	Package	Marking	Packaging
G33N03S	SOP-8	G33N03	4000pcs/Reel

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Continuous Drain Current	I_D	13	A
Pulsed Drain Current (note1)	I_{DM}	50	A
Gate-Source Voltage	V_{GS}	± 20	V
Power Dissipation	P_D	2.5	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	$^\circ\text{C}$

Thermal Resistance


Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	50	$^\circ\text{C/W}$

Specifications T _j = 25°C, unless otherwise noted						
Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	30	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 0V	--	--	1	μA
Gate-Source Leakage	I _{GSS}	V _{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	0.5	0.9	1.1	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 8A	--	9	12	mΩ
		V _{GS} = 4.5V, I _D = 8A	--	10.5	13	
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1.0MHz	--	1550	--	pF
Output Capacitance	C _{oss}		--	300	--	
Reverse Transfer Capacitance	C _{rss}		--	180	--	
Total Gate Charge	Q _g	V _{DD} = 15V, I _D = 8A, V _{GS} = 5V	--	13	--	nC
Gate-Source Charge	Q _{gs}		--	5.5	--	
Gate-Drain Charge	Q _{gd}		--	3.5	--	
Turn-on Delay Time	t _{d(on)}	V _{DD} = 15V, I _D = 8A, R _G = 3Ω	--	30	--	ns
Turn-on Rise Time	t _r		--	20	--	
Turn-off Delay Time	t _{d(off)}		--	100	--	
Turn-off Fall Time	t _f		--	80	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I _S	T _C = 25°C	--	--	13	A
Body Diode Voltage	V _{SD}	T _j = 25°C, I _{SD} = 8A, V _{GS} = 0V	--	--	1.2	V


Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. Identical low side and high side switch with identical R_G


Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Gate Charge




Figure 4. Drain Source On Resistance




Figure 5. Capacitance





Figure 6. Source-Drain Diode Forward



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. Drain-Source On-Resistance




Figure 8. Safe Operation Area






Figure 9. Normalized Maximum Transient Thermal Impedance



SOP-8 Package Information



COMMON DIMENSIONS
(UNITS OF MEASURE=mm)

SYMBOL	MIN	NOM	MAX
A	1.40	1.60	1.80
A1	0.05	0.15	0.25
A2	1.35	1.45	1.55
b	0.30	0.40	0.50
c	0.153	0.203	0.253
D	4.80	4.90	5.00
E	3.80	3.90	4.00
E1	5.80	6.00	6.20
L	0.45	0.70	1.00
θ	2°	4°	6°
L 1	1.04 REF		
e	1.27 BSC		
R1	0.07 TYP		
R2	0.07 TYP		