



Connectors > Contacts > Connector Contacts



Contact Type: **Socket**

Contact Mating Area Plating Material: **Gold**

Wire Contact Termination Area Plating Material: **Tin**

Operating Voltage: **300 VAC**

Compatible With Wire & Cable Type: **Discrete Wire**

Features

Product Type Features

Applied Pressure	Standard
------------------	----------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Electrical Characteristics

Termination Resistance	12 mΩ
Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 V
Operating Voltage	300 VAC

Contact Features

Mating Square Post Dimension	.64 mm[.025 in]
Contact Type	Socket
Contact Mating Area Plating Material	Gold
Wire Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy



Contact Current Rating (Max)	3 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Compatible Insulation Diameter Range	.64 - 1.52 mm[.025 - .06 in]
Wire Size	59.2 - 177.62 CMA
Usage Conditions	
Operating Temperature Range	-65 - 105 °C[-85 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Compatible With Approved Standards Products	CSA LR7189, UL E28476
Packaging Features	
Packaging Quantity	15000
Packaging Method	Reel
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 91518-1 CCII AMPMODU SHORT POINT REC 32-22 ASSY	TE Part # 843477-1 TOOL, EXTRACTION RESET	TE Part # 1-104482-8 40 SHORT PT RCPT HSG DR .100CL	TE Part # 104483-4 26 SHORT PT RCPT HSG DR .100CL
TE Part # 104483-5 30 SHORT PT RCPT HSG DR .100CL	TE Part # 104257-9 10 MTE RCPT HSG SR LATCH .100	TE Part # 1-104257-3 14 MTE RCPT HSG SR LATCH .100	TE Part # 104257-6 07 MTE RCPT HSG SR LATCH .100
TE Part # 104257-7 08 MTE RCPT HSG SR LATCH .100	TE Part # 1-104257-5 16 MTE RCPT HSG SR LATCH .100	TE Part # 104257-2 03 MTE RCPT HSG SR LATCH .100	TE Part # 104257-5 06 MTE RCPT HSG SR LATCH .100
TE Part # 103648-7 08 MTE RCPT HSG SR RIB .100CL	TE Part # 104257-3 04 MTE RCPT HSG SR LATCH .100	TE Part # 104257-1 02 MTE RCPT HSG SR LATCH .100	TE Part # 104257-4 05 MTE RCPT HSG SR LATCH .100





TE Part # 104482-3
08 SHORT PT RCPT HSG DR .100CL



TE Part # 1-104257-1
12 MTE RCPT HSG SR LATCH .100



TE Part # 104257-8
09 MTE RCPT HSG SR LATCH .100




TE Part # 104482-4
10 SHORT PT RCPT HSG DR .100CL

Also in the Series | AMPMODU IV/V



Automotive Housings(1)




Backplane Connector Housings(1)



Connector Caps & Covers(18)



Connector Contacts(321)




Connector Hardware(13)



Connector Strain Relief(3)



Insertion & Extraction Tools(4)



PCB Headers & Receptacles(931)



Rectangular Connector Housings(5)



Standard Rectangular Connectors(8)



Wire-to-Board Connector Assemblies & Housings(444)

Customers Also Bought



TE Part # 66505-4
HD 20 DF SOCKET PLTD



TE Part # 5-104363-5
06 MTE HDR SRST LATCH .100CL




TE Part # 104257-5
06 MTE RCPT HSG SR LATCH .100



TE Part # 104257-3
04 MTE RCPT HSG SR LATCH .100



TE Part # 2-1445093-4
MICRO MNL HDR ASSY S/ROW AU LF



TE Part # 5-104506-4
MTE PIN 28-32 AWG PLTD



TE Part # 104482-4
10 SHORT PT RCPT HSG DR .100CL



TE Part # 51863-3
TERM,RING, PIDG, IR, 20, #6



TE Part # 640383-4
04P MTA156 HDR ASSY STR SQ SN



TE Part # 5-103960-3
5X4 MTE RCPT SR LATCH .100CL

Documents

Product Drawings

SHORT POINT CONT 15 DPLX STMPD LF

English

CAD Files

Customer View Model

ENG_CVM_1-104481-0_N.2d_dxf.zip

English

3D PDF

English

Customer View Model

ENG_CVM_1-104481-0_N.3d_igs.zip

English

Customer View Model

ENG_CVM_1-104481-0_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT

English

AMPMODU MTE INTERCONNECT SYSTEM

English

Product Specifications

Application Specification

English

BA1-104481-0

Socket Contact, Gold, 300 VAC, Discrete Wire, 32 - 28 AWG Wire Size, .03 - .09 mm² Wire Size, 59.2 - 177.62 CMA Wire Size, Crimp, AMPMODU IV/V

