




Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1624 - 4106 CMA

Stud Size: #8, M4

Features

Product Type Features

|                                        |                             |
|----------------------------------------|-----------------------------|
| Shape Description                      | Circular/Oval               |
| Ring Terminal Product Type             | Closed Ring Tongue Terminal |
| Stud Size                              | #8, M4                      |
| Sealable                               | No                          |
| Compatible With Discrete Wire Type     | Stranded                    |
| Wire Insulation Support Retention Type | Insulation Support          |

Configuration Features

|                 |   |
|-----------------|---|
| Number of Holes | 1 |
|-----------------|---|

Contact Features

|                               |          |
|-------------------------------|----------|
| Contact Base Material         | Brass    |
| Barrel Type                   | Open     |
| Terminal Orientation          | Straight |
| Terminal Plating Material     | Tin      |
| Contact Underplating Material | Nickel   |

Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|



Dimensions

|                                      |                                   |
|--------------------------------------|-----------------------------------|
|                                      | .1 in                             |
| Wire Size                            | 1624 - 4106 CMA                   |
| Stud Diameter                        | 4.34 mm[.171 in]                  |
| Tongue Thickness                     | .76 mm[.03 in]                    |
| Product Length                       | 19.81 mm[.78 in]                  |
| Barrel Inside Diameter               | 1.77 mm, 2.92 mm[.07 in][.115 in] |
| Compatible Insulation Diameter (Max) | 3.56 mm[.14 in]                   |
| Compatible Insulation Diameter Range | 2.54 - 3.56 mm[.1 - .14 in]       |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Uninsulated                |
| Operating Temperature Range | -40 - 110 °C[-40 - 230 °F] |

Operation/Application

|                                    |        |
|------------------------------------|--------|
| Compatible With Wire Base Material | Copper |
|------------------------------------|--------|

Industry Standards

|                               |    |
|-------------------------------|----|
| Government Qualified Terminal | No |
|-------------------------------|----|

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 11000      |
| Packaging Method   | Strip/Reel |

Product Compliance

For compliance documentation, visit the product page on TE.com>



|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240)<br>Candidate List Declared Against: JAN 2024 (240)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                  |



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts

|                                                                                                                                                    |                                                                                                                                                          |                                                                                                                                                          |                                                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 42933-2<br/>RING TERMINAL 20-16 AWG TPBR</p>      |  <p>TE Part # 61359-1<br/>RING GR ANTI ROTATIONAL 18-14 AWG PTPST</p> |  <p>TE Part # 2150355-1<br/>OCEAN_2.0_Applicator-E-130F180F-REM</p> |  <p>TE Part # 2150355-2<br/>OCEAN_2.0_Applicator-E-130F180F-REA</p> |
|  <p>TE Part # 63170-1<br/>RING TERMINAL (RT) 18-14 AWG TPBR</p> |  <p>TE Part # 7-2150355-7<br/>OCEAN_2.0_SPARE_PART_KIT-130F180F</p>   |  <p>TE Part # 7-2150355-1<br/>OCEAN_2.0_Applicator-E-130F180F</p>   |  <p>TE Part # 7-2150355-2<br/>OCEAN_2.0_Applicator-E-130F180F</p>   |


Customers Also Bought

|                                                                                                                                      |                                                                                                                                           |                                                                                                                                           |                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 3-1393250-7<br/>W28-XQ1A-4=W28-</p> |  <p>TE Part # 33458<br/>TERMINAL,SOLIS R 12-10 1/4</p> |  <p>TE Part # 32994<br/>TERMINAL,SOLIS R 12-10 8</p> |  <p>TE Part # 34319<br/>SPLICE,SOLIS PARA 6</p> |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|






TE Part # 34318  
SPLICE, SOLIS PARA 8



TE Part # 34138  
SPLICE, SOLIS PARA 12-10




TE Part # 2-520405-2  
ULTRA-FAST 250 ASY REC 22-18 TPBR



TE Part # 2-520102-2  
ULTRA-FAST 250 ASSEMBLY TAB 22-18 AWG BR



TE Part # 2-520128-2  
ULTRA-FAST 250 ASY REC 22-18 AWG TPBR



TE Part # 2-521308-2  
205 ULTRA-FAST RCPT 22-18 TPBR

Documents

Product Drawings

RING CRIMP TAB 18-14 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_60024-2\_S\_c-60024-2-s.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_60024-2\_S\_c-60024-2-s.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_60024-2\_S\_c-60024-2-s.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Engineering Report

English