

Reflective Optical Sensor With VCSEL and Transistor Output



LINKS TO ADDITIONAL RESOURCES


[Application Notes](#)

[3D Models](#)

FEATURES

- Package type: SMD
- Detector type: phototransistor
- Dimensions (L x W x H in mm): 1.85 x 1.2 x 0.6
- Emitter wavelength: 940 nm
- Moisture sensitivity level (MSL): 3
- Material categorization:
for definitions of compliance please see
www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN FREE
GREEN
(S-2008)

APPLICATIONS

- Position sensor
- Optical switch
- Optical encoder
- Object detection (e.g. paper presence in printer and copy machines)

DESCRIPTION

The VCNT2030 is a reflective sensor in a miniature SMD package. It has a compact construction where the emitting light source and the detector are arranged in the same plane. The emitter uses a vertical cavity surface emitting laser (VCSEL) chip technology with high radiant intensity, high optical power, and high speed. The operating infrared wavelength is 940 nm. The detector consists of a silicon phototransistor. The sensor's analog output signal at the phototransistor is dependent on the amount of the light emitted by the VCSEL and reflected off of an object in the sensor's field of view.

PRODUCT SUMMARY					
PART NUMBER	TARGET MATERIAL	DISTANCE RANGE WITH $I_{F\max.}$ AND $I_C > 0.5$ mA (mm)	TYPICAL CTR ⁽¹⁾ (%)	DISTANCE OF PEAK SENSITIVITY (mm)	DAYLIGHT BLOCKING FILTER INTEGRATED
VCNT2030	Kodak Gray Card, gray side (18 %)	0 to 7	31	0.9	No
	Kodak Gray Card, white side (90 %)	0 to 38	314		

Note

⁽¹⁾ CTR: current transfer ratio, $I_{\text{out}}/I_{\text{in}}$

ORDERING INFORMATION			
ORDERING CODE	PACKAGING	VOLUME ⁽¹⁾	REMARKS
VCNT2030	Tape and reel	MOQ: 3000	Drypack, MSL 3

Note

⁽¹⁾ MOQ: minimum order quantity

ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25 \text{ }^{\circ}\text{C}$, unless otherwise specified)				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
INPUT (VCSEL)				
Reverse voltage		V_R	5	V
Forward current		I_F	15	mA
Power dissipation		P_{VCSEL}	38	mW
Junction temperature		T_J	100	$^{\circ}\text{C}$
Thermal resistance junction to ambient	JESD 51	R_{thJA}	410	K/W
OUTPUT (DETECTOR)				
Collector emitter breakdown voltage	$I_C = 0.1 \text{ mA}, E = 0$	$V_{(BR)CEO}$	20	V
Emitter collector voltage		V_{ECO}	7	V
Collector current		I_C	50	mA
Power dissipation		P_{PTR}	100	mW
Thermal resistance junction to ambient	JESD 51	R_{thJA}	380	K/W
SENSOR				
Total power dissipation		P_{tot}	138	mW
Ambient temperature range		T_{amb}	-40 to +85	$^{\circ}\text{C}$
Storage temperature range		T_{stg}	-40 to +85	$^{\circ}\text{C}$
Soldering temperature	In accordance with Fig. 14	T_{sd}	260	$^{\circ}\text{C}$




Fig. 1 - Power Dissipation vs. Ambient Temperature

BASIC CHARACTERISTICS ($T_{amb} = 25^\circ\text{C}$, unless otherwise specified)						
PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
INPUT (VCSEL)						
Forward current ⁽¹⁾		I_F	-	5	-	mA
Forward voltage	$I_F = 8 \text{ mA}$	V_F	1.7	1.9	2.1	V
	$I_F = 15 \text{ mA}$		-	2.3	-	
Temperature coefficient of V_F	$I_F = 8 \text{ mA}$	TKV_F	-	-4	-	mV/K
Angle of half intensity	$I_F = 8 \text{ mA}$	φ	-	17	-	°
Reverse current		I_R	Not designed for reverse operation			
Peak wavelength	$I_F = 8 \text{ mA}$	λ_P	-	940	-	nm
OUTPUT (DETECTOR)						
Emitter collector voltage	$I_E = 100 \mu\text{A}$, $E = 0$	V_{ECO}	7	-	-	V
Collector emitter dark current	$V_{CE} = 5 \text{ V}$, $E = 0$	I_{CEO}	-	1	100	nA
SENSOR						
Collector current	$V_{CE} = 5 \text{ V}$, $I_F = 8 \text{ mA}$, $d = 1 \text{ mm}$ (Kodak gray card, 18 %)	I_C	1.8	2.5	5.4	mA
	$V_{CE} = 5 \text{ V}$, $I_F = 8 \text{ mA}$, $d = 1 \text{ mm}$ (Kodak gray card, white side, 90 %)	I_C	-	25.1	-	mA
Current transfer ratio	I_C/I_F , $V_{CE} = 5 \text{ V}$, $d = 1 \text{ mm}$ (Kodak gray card, 18 %)	CTR	-	31	-	%
Rise time	$I_C = 0.8 \text{ mA}$, $V_{CE} = 5 \text{ V}$, $R_L = 100 \Omega$	t_r	-	10	-	μs
Fall time	$I_C = 0.8 \text{ mA}$, $V_{CE} = 5 \text{ V}$, $R_L = 100 \Omega$	t_f	-	15	-	μs

Note

⁽¹⁾ It is recommended to apply at least 5 mA forward current, to ensure expected device performance




Fig. 2 - Test Circuit


BASIC CHARACTERISTICS ($T_{amb} = 25$ °C, unless otherwise specified)


Fig. 3 - Forward Voltage vs. Forward Current




Fig. 6 - Collector Current vs. Forward Current




Fig. 4 - Forward Voltage vs. Ambient Temperature




Fig. 7 - Relative Collector Current vs. Ambient Temperature




Fig. 5 - Collector Dark Current vs. Ambient Temperature




Fig. 8 - Relative Radiant Intensity vs. Angular Displacement




Fig. 9 - Relative Sensitivity vs. Angular Displacement




Fig. 12 - Rise / Fall Time vs. Collector Current




Fig. 10 - Relative Spectral Sensitivity vs. Wavelength




Fig. 13 - Relative Collector Current vs. Distance




Fig. 11 - Relative Collector Current vs. Displacement

FLOOR LIFE

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:

Moisture sensitivity: level 3

Floor life: 168 h

Conditions: $T_{amb} < 30^{\circ}\text{C}$, RH < 60 %

DRYING

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or recommended conditions:

192 h at 40°C (+ 5 °C), RH < 5 %


or

96 h at 60°C (+ 5 °C), RH < 5 %

PRECAUTIONS - EYE SAFETY

When VCSEL is in operation, looking into laser beam directly by naked eyes, even through a lens, microscope or optical fibers, may cause severe damage to human eyes. For observing laser beams, using safety goggles is recommended.


LABEL FOR LASER CLASS 1



Note


- Product specification with IEC / EN 60825-1:2014 compliance and above label

REFLOW SOLDER PROFILE




19841

Fig. 14 - Lead (Pb)-free Reflow Solder Profile
According to J-STD-020

PACKAGE DIMENSIONS in millimeters


TAPE AND REEL DIMENSIONS in millimeters

3000 pcs/reel


 Drawing No.: 9.800-5149.01-4
 Issue: 1; 05.12.2019

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.