

APPLICABLE STANDARD		SPECIFICATIONS												
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTES 1)		STORAGE TEMPERATURE RANGE	-10°C TO + 60°C									
	VOLTAGE	50V AC		APPLICABLE CONNECTOR	DF17# (**)-*DS-0.5V (**)									
	CURRENT	0.3A												
CONSTRUCTION														
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.										
MARKING		CONFIRMED VISUALLY.												
ELECTRIC CHARACTERISTICS														
CONTACT RESISTANCE		100mA (DC OR 1000 Hz).		60mΩ MAX.										
INSULATION RESISTANCE		100V DC.		500MΩ MIN.										
VOLTAGE PROOF		150V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.										
MECHANICAL CHARACTERISTICS														
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.			<table border="1"> <thead> <tr> <th>SIGNAL</th><th>INSERTION FORCE (N)MAX</th><th>WITHDRAWAL FORCE (N)MIN</th></tr> </thead> <tbody> <tr> <td>26</td><td>26.0</td><td>2.6</td></tr> <tr> <td>80</td><td>80.0</td><td>8.0</td></tr> </tbody> </table>	SIGNAL	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN	26	26.0	2.6	80	80.0	8.0	X
SIGNAL	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN												
26	26.0	2.6												
80	80.0	8.0												
MECHANICAL OPERATION		50TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X									
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.										
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X									
ENVIRONMENTAL CHARACTERISTICS														
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5 TO 35 → 85 → 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X									
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X									
CORROSION SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X									
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39)		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X									
HEAT RESISTANCE OF SOLDERING		[RECOMMENDED TEMPERATURE PROFILE] 『SOLDERING AREA』 MAX250°C, 220°C FOR 60 SECONDS MAX. 『PREHEATING AREA』 150 TO 180°C 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDERING CONDITION ] SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.										
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED									
					DATE									
REMARKS NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT.				APPROVED	MO.NAKAMURA 05.04.05									
				CHECKED	TS.MIYAZAKI 05.04.05									
				DESIGNED	YH.MICHIDA 05.04.05									
UNLESS OTHERWISE SPECIFIED,REFER TO JIS C 5402.				DRAWN	YH.MICHIDA 05.04.05									
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-163274-04									
	SPECIFICATION SHEET		PART NO.	DF17 (2.5) -*DP-0.5V (57)										
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL683	1/1									