

APPLICABLE STANDARD		SPECIFICATIONS						
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTES 1)		STORAGE TEMPERATURE RANGE	-10°C TO + 60°C			
	VOLTAGE	50V AC		APPLICABLE CONNECTOR	DF17# (**)-*DS-0.5V (57)			
	CURRENT	0.3A						
CONSTRUCTION								
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.			X X		
MARKING	CONFIRMED VISUALLY.					X X		
ELECTRIC CHARACTERISTICS								
CONTACT RESISTANCE	100m A (DC OR 1000 Hz).		60mΩ MAX.			X -		
INSULATION RESISTANCE	100V DC.		500MΩ MIN.			X -		
VOLTAGE PROOF	150V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.			X -		
MECHANICAL CHARACTERISTICS								
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.			PIN COUNT	INSERTION FORCE	WITHDRAWAL FORCE		
					(N)MAX	(N)MIN		
				30	30.0	3.0		
				40	40.0	4.0		
				50	50.0	5.0		
				60	60.0	6.0		
				80	80.0	8.0		
MECHANICAL OPERATION	50TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X -		
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X -		
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X -		
ENVIRONMENTAL CHARACTERISTICS								
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→ 85→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X -		
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X -		
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			X -		
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39)		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			X -		
HEAT RESISTANCE OF SOLDERING	【RECOMMENDED TEMPERATURE PROFILE】 『SOLDERING AREA』 MAX250°C, 220°C FOR 60 SECONDS MAX. 『PREHEATING AREA』 150 TO 180°C 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. 【RECOMMENDED MANUAL SOLDERING CONDITION】 SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			X -		
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE		
1	DIS-H-00003088		SH. HOSODA		TS. MIYAZAKI	17. 09. 29		
REMARKS NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT. UNLESS OTHERWISE SPECIFIED,REFER TO JIS C 0806.				APPROVED	M0. NAKAMURA	05. 05. 20		
				CHECKED	TS. MIYAZAKI	05. 05. 19		
				DESIGNED	YH. MICHIDA	05. 05. 19		
				DRAWN	YH. MICHIDA	05. 05. 19		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-162140-06			
HRS	SPECIFICATION SHEET		PART NO.	DF17A (4. 0)-*DP-0. 5V (57)				
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL683		△ 1/1		