




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.51 - 1.31 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	2.1 mm[.083 in]
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.51 mm[.02 in]
Product Length	20.5 mm[.807 in]
Compatible Insulation Diameter Range	2.01 - 3 mm[.079 - .118 in]
Wire Size	.51 - 1.31 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 62447-2 AMVAR FF 187 TAB 22-16AWG TPBR	 TE Part # 160719-3 FASTIN FASTON (FF) TAB 20/16 AWG BR	 TE Part # 2150073-1 OCEAN_2.0_Applicator-E-100F140F-REM	 TE Part # 2150073-2 OCEAN_2.0_Applicator-E-100F140F-REA
 TE Part # 62443-1 AMVAR FF 187 TAB 12-10AWG TPBR	 TE Part # 7-2150073-7 OCEAN_2.0_SPARE_PART_KIT-100F140F	 TE Part # 7-2150073-1 OCEAN_2.0_Applicator-E-100F140F	 TE Part # 7-2150073-2 OCEAN_2.0_Applicator-E-100F140F

Also in the Series | FASTIN-FASTON 110

 Automotive Housings(6)	 Automotive Terminals(5)	 Crimp Terminal Housings(34)	 Insertion & Extraction Tools(3)
 Quick Disconnects(83)			

Customers Also Bought






TE Part # 2236793-3
SMARTSEAL TERMINAL



TE Part # 1-2291193-3
SMARTSEAL TERMINAL



TE Part # 1333216-4
ANVIL EF .080



TE Part # 2-1490019-1
CRIMPER, WIRE (.100" 'F')



TE Part # 2-1633127-6
ANVIL, COMBINATION .042



TE Part # 2-1803334-0
ANVIL, COMBINATION



TE Part # 2151147-1
OCEAN-2.0-APPLICATOR-S-042F042O-RSM



TE Part # 2305881-1
CVTY PLUG, 090 SERIES, CVTY DIA, 1, GRY



TE Part # 240833-1
PLATE, REAR SHEAR



TE Part # 454712-6
PLATE, REAR SHEAR

Documents

Product Drawings

FF 110 TAB 20-16AWG PTBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_170014-6_AP.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170014-6_AP.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170014-6_AP.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

170014-6

Quick Disconnects, Tab, 20 - 16 AWG Wire Size, .51 - 1.31 mm² Wire Size, Mating Tab
Width 2.8 mm [.11 in], Straight, Brass, FASTIN-FASTON 110



Product Specification

English