

**1-338088-6**  ACTIVE

TE Internal #: 1-338088-6

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks &amp; Plugs, Standard Connector Contact Density, Jack, Cat 3, Standard - Latch Down, 8 Position

[View on TE.com >](#)

Connectors &gt; Modular Jacks &amp; Plugs &gt; RJ45 Connectors

Modular Jack & Plug Interface Type: **RJ45**Port Configuration: **Single Port**Port Matrix Configuration: **1 x 1**Modular Jacks & Plugs Products: **RJ Type Jacks & Plugs**Connector Contact Density: **Standard**

## Features

### Product Type Features

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	None
Connector & Contact Terminates To	Printed Circuit Board

### Configuration Features

Port Configuration	Single Port
Port Matrix Configuration	1 x 1
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	8
PCB Mount Orientation	Vertical

### Body Features

Modular Jack Latch Orientation

Standard - Latch Down

Connector Profile

Standard

**Contact Features**

PCB Contact Termination Area Plating Material

Tin

Contact Current Rating (Max)

1.5 A

Contact Mating Area Plating Material

Gold (Au)

Contact Base Material

Phosphor Bronze

Contact Mating Area Plating Material Thickness

1.27 µm[50 µin]

**Termination Features**

Termination Method to Printed Circuit Board

Surface Mount

Termination Post &amp; Tail Length

1.5 mm[.059 in]

**Mechanical Attachment**

Panel Mount Feature

Without

Connector Mounting Type

Board Mount

**Housing Features**

Mating Entry Location

Top

Centerline (Pitch)

1.02 mm[.04 in]

Housing Color

Black

Housing Material

PA 4T GF30

**Dimensions**

PCB Thickness (Recommended)

1.57 mm[.062 in]

Connector Height

12.7 mm[.5 in]

**Usage Conditions**

Operating Temperature Range

-45 - 70 °C[-40 - 158 °F]

**Operation/Application**

Indicator Type

Not Illuminated

Shielded

No

Circuit Application

Signal

**Industry Standards**

UL Flammability Rating

UL 94V-0

Performance Category

Cat 3

**Packaging Features**

Packaging Quantity	250
Packaging Method	Reel

## Product Compliance


For compliance documentation, visit the product page on [TE.com](https://te.com)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 260°C


### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



## Customers Also Bought



## Documents

### Product Drawings

#### 8/8 INV.MOD.JACK

English

### CAD Files

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1-338088-6\\_Z.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1-338088-6\\_Z.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_1-338088-6\\_Z.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

[\*\*AMP surface mount modular jack\*\*](#)

English

[\*\*Application Specification\*\*](#)

English

---

[\*\*Agency Approvals\*\*](#)

[\*\*UL Report\*\*](#)

English