

1-1393154-3  ACTIVE

TE Internal #: 1-1393154-3

Power Relays, Industrial Panel Plug-In, Monostable, 750 mW Coil

Power Rating DC, 20833 Ω Coil Resistance, UL Coil Insulation Class

F

[View on TE.com >](#)

Relays & Contactors > Relays > Power Relays

Relay Type: **Industrial Panel Plug-In**Coil Magnetic System: **Monostable**Coil Power Rating DC: **750 mW**Coil Resistance: **20833 Ω**Coil Special Features: **UL Coil Insulation Class F**

Features

Product Type Features

Relay Type	Industrial Panel Plug-In
------------	--------------------------

Configuration Features

Insulation Special Features	5000V Initial Surge Withstand Voltage between Contacts & Coil
-----------------------------	---

Coil Special Features	UL Coil Insulation Class F
-----------------------	----------------------------

Contact Arrangement	4 Form C (4 CO)
---------------------	-----------------

Contact Number of Poles	4
-------------------------	---

Electrical Characteristics

Insulation Initial Dielectric Between Open Contacts	1200 Vrms
---	-----------

Contact Limiting Making Current	12 A
---------------------------------	------

Contact Limiting Short-Time Current	300 A
-------------------------------------	-------

Insulation Initial Dielectric Between Adjacent Contacts	2000 Vrms
---	-----------

Insulation Initial Dielectric Between Contacts & Coil	2500 Vrms
---	-----------

Contact Limiting Breaking Current	6 A
-----------------------------------	-----

Coil Power Rating DC	750 mW
----------------------	--------

Coil Resistance	20833 Ω
-----------------	---------

Coil Voltage Rating	125 VDC
---------------------	---------

Contact Current Rating	6 A
------------------------	-----

Contact Switching Load (Min)	10mA @ 12V
------------------------------	------------

Contact Switching Voltage (Max)	240 VAC
---------------------------------	---------

Contact Voltage Rating	240 VAC
------------------------	---------

Body Features

Product Weight	30 g[1.058 oz]
----------------	----------------

Contact Features

Contact Material	AgNi90/10
------------------	-----------

Termination Features

Relay Connection Type	Plug-In
-----------------------	---------

Mechanical Attachment

Product Mount Type	Socket
--------------------	--------

Dimensions

Insulation Clearance Between Contact & Coil	3 mm
---	------

Insulation Creepage Between Contact & Coil	4 mm[.157 in]
--	---------------

Product Width	22.5 mm[.885 in]
---------------	------------------

Product Length	28 mm[1.1 in]
----------------	---------------

Product Height	29 mm[1.14 in]
----------------	----------------

Usage Conditions

Environmental Ambient Temperature (Max)	70 °C[158 °F]
---	---------------

Operating Temperature Range	-40 - 70 °C
-----------------------------	-------------

Operation/Application

Actuating System	DC
------------------	----

Coil Magnetic System	Monostable
----------------------	------------

Packaging Features

Packaging Method	Carton & Tube
------------------	---------------

Other

Length Class (Mechanical)	25 - 30 mm
---------------------------	------------

Insulation Creepage Class	3 - 5.5 mm
---------------------------	------------

Insulation Clearance Class	2.5 - 4 mm
----------------------------	------------

Height Class (Mechanical)	25 - 30 mm
---------------------------	------------

Coil Power Rating Class	600 - 800 mW
-------------------------	--------------

Width Class (Mechanical)	20 - 25 mm
--------------------------	------------

Contact Current Class

5 - 10 A

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Hand solderable with lead free solder

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts





Customers Also Bought





Documents

CAD Files

[3D PDF](#)

3D

[Customer View Model](#)

[ENG_CVM_CVM_1-1393154-3_99.2d_dxf.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_1-1393154-3_99.3d_igs.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_1-1393154-3_99.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Miniature Relay PT](#)

English

Product Specifications

[Definitions General Purpose Relays](#)

English

Agency Approvals

[UL](#)

English