

6-535512-4  ACTIVE

## AMPMODU | Modu Connector System


TE Internal #: 6-535512-4

PCB Mount Receptacle, Right Angle, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Gold, Through Hole - Solder, Signal, Modu Connector System

[View on TE.com >](#)



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **10**

Number of Rows: **2**

## Features

### Product Type Features

Applied Pressure	High, Standard
PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

### Configuration Features

Stackable	Yes
PCB Mount Orientation	Right Angle
Number of Positions	10
Number of Rows	2

### Electrical Characteristics

Dielectric Withstanding Voltage (Max)	750 VAC
Insulation Resistance	5000 MΩ
Operating Voltage	333 VAC

### Body Features

Connector Profile	Standard
Primary Product Color	Black

### Contact Features

Contact Protection Type	Closed Entry Housing
Contact Mating Area Length	3 mm [.1 in]
Mating Square Post Dimension	.64 mm [.025 in]
	10 $\mu$ in
Contact Shape & Form	Short Point
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.762 $\mu$ m [30 $\mu$ in]
Contact Type	Socket
Contact Current Rating (Max)	2 A

#### Termination Features

Rectangular Termination Post & Tail Thickness	.2 mm [.008 in]
Rectangular Termination Post & Tail Width	.69 mm [.027 in]
Termination Post & Tail Length	2.92 mm [.115 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

#### Mechanical Attachment

Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount

#### Housing Features

Mating Entry Location	Side
Centerline (Pitch)	2.54 mm [.1 in]
Housing Material	Polyester - GF

#### Dimensions

Connector Height	6.05 mm [.238 in]
Row-to-Row Spacing	2.54 mm, 7.87 mm [.31 in]
Stack Height	8.13 mm [.32 in]
PCB Thickness (Recommended)	1.4 - 2.4 mm [.055 - .094 in]

#### Usage Conditions

Housing Temperature Rating	High
----------------------------	------

Operating Temperature Range -65 - 105 °C[-85 - 221 °F]

### Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Signal

### Industry Standards

Compatible With Approved Standards Products	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0

### Packaging Features

Packaging Quantity	45
Packaging Method	Box, Tube

### Product Compliance

For compliance documentation, visit the product page on [TE.com](http://TE.com)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts




TE Part # 87215-2  
 10 MODII HDR DRST UNSHRD .100


TE Part # 86479-3  
 10 MODII HDR DRRA UNSHRD .100

## Also in the Series


## Modu Connector System




Automotive Connector Caps & Covers (3)




Automotive Housings(1)



Board-to-Board Jumpers & Shunts(5)




Connector Caps & Covers(1)



Connector Hardware(4)



PCB Headers & Receptacles(1244)



Standard Edge Connectors(1)

## Customers Also Bought



TE Part # 1625971-5  
 HSA25 10R 5%



TE Part # 103166-5  
 14 MODII HDR DRRA SHRD .100CL




TE Part # 5745854-1  
 CABLE CLAMP KIT,SZ 1



TE Part # 1-216602-0  
 10P HV190 FEDERLEIS



TE Part # 5-2176367-6  
 RQ 0603 17K4 0.1% 10PPM 1K RL



TE Part # 446852-1  
 3 ROW BOX PIN 90P R/A SEALED



TE Part # 4-1879387-5  
 MGDDQ5-00017,S-L100lmax1.3

## Documents

### Product Drawings

[10 MODII HORZ DR CE EESS .100](#)

English

---

### CAD Files

[3D PDF](#)

English

[Customer View Model](#)

[ENG\\_CVM\\_6-535512-4\\_Y1.3d\\_stp.zip](#)

English

[Customer View Model](#)

[ENG\\_CVM\\_6-535512-4\\_Y1.3d\\_igs.zip](#)

English

[Customer View Model](#)

[ENG\\_CVM\\_6-535512-4\\_Y1.2d\\_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

### Product Specifications

[Application Specification](#)

English