




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **6**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Rectangular Power Connector Type  | Header                |
| Connector & Housing Type          | Plug                  |
| Connector System                  | Wire-to-Board         |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

|                           |          |
|---------------------------|----------|
| Number of Positions       | 6        |
| PCB Mount Orientation     | Vertical |
| Number of Power Positions | 6        |
| Number of Rows            | 2        |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 600 VAC |
|-------------------|---------|

Contact Features

|                        |         |
|------------------------|---------|
| Multiple Contact Types | Without |
|------------------------|---------|



|                                                |                               |
|------------------------------------------------|-------------------------------|
| Contact Layout                                 | Matrix                        |
| Contact Mating Area Plating Material           | Tin                           |
| Contact Current Rating (Max)                   | 12 A                          |
| Contact Retention Within Housing               | Without                       |
| Contact Type                                   | Socket                        |
| PCB Contact Termination Area Plating Material  | Pre-Tin                       |
| Contact Mating Area Plating Material Thickness | 3.81 - 5.08 µm[150 - 200 µin] |

Termination Features

|                                             |                       |
|---------------------------------------------|-----------------------|
| Termination Post & Tail Length              | 3.81 mm[.149 in]      |
| Termination Method to Printed Circuit Board | Through Hole - Solder |

Mechanical Attachment

|                          |                         |
|--------------------------|-------------------------|
| PCB Mount Alignment Type | Standard Polarized Tail |
| Strain Relief            | Without                 |
| Mating Alignment Type    | Polarization            |
| Mating Retention         | With                    |
| Mating Alignment         | With                    |
| PCB Mount Alignment      | With                    |
| Panel Mount Feature      | Without                 |
| PCB Mount Retention      | Without                 |
| Mating Retention Type    | Positive Lock           |
| Connector Mounting Type  | Board Mount             |

Housing Features

|                    |                 |
|--------------------|-----------------|
| Centerline (Pitch) | 6.35 mm[.25 in] |
| Housing Color      | Natural         |
| Housing Material   | Nylon           |

Dimensions

|                             |                  |
|-----------------------------|------------------|
| Connector Height            | 13.97 mm         |
| PCB Thickness (Recommended) | 3.18 mm[.125 in] |
| Product Width               | 20.32 mm         |
| Product Length              | 20.32 mm         |
| Row-to-Row Spacing          | 6.35 mm[.25 in]  |

Usage Conditions

|  |  |
|--|--|
|  |  |
|--|--|



|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 - 105 °C[-40 - 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |       |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

Industry Standards

|                                             |                               |
|---------------------------------------------|-------------------------------|
| CSA Rating                                  | Certified, LR 7189            |
| UL Rating                                   | Recognized                    |
| Compatible With Agency/Standards Products   | CSA, UL, VDE                  |
| Compatible With Approved Standards Products | UL E28476                     |
| UL Flammability Rating                      | UL 94V-0                      |
| Glow Wire Rating                            | Standard Part - Not Glow Wire |

Packaging Features

|                    |           |
|--------------------|-----------|
| Packaging Quantity | 100       |
| Packaging Method   | Bag & Box |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240)<br>Candidate List Declared Against: JAN 2024 (240)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                                  |





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


|                                                                                                                                              |                                                                                                                                                |                                                                                                                                               |                                                                                                                                              |
|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <br>TE Part # 350812-1<br>STR/REL CLAMP UMNL                | <br>TE Part # 640715-1<br>06P UMNL STR/REL                    | <br>TE Part # 1-350590-0<br>STR/REL CLAMP NATL             | <br>TE Part # 1586860-1<br>06P UMNL CAP HSG, GW           |
| <br>TE Part # 1-640721-0<br>06P UMNL STR/REL & INSRT NATL | <br>TE Part # 770020-1<br>06P UMNLII IN-LNE PLUG HSG KIT    | <br>TE Part # 926682-3<br>06P UNIV.M-N-L.HSG.            | <br>TE Part # 350715-1<br>06P UMNL PLUG HSG             |
| <br>TE Part # 794536-1<br>06P UMNL CAP HSG 150C BLK       | <br>TE Part # 1969814-1<br>06P UMNL PIN HDR ASSY, PIN V0 GW | <br>TE Part # 2029367-1<br>06P UMNL-II TW-N-LK-CAP FRONT | <br>TE Part # 926682-1<br>UNIVERSAL M-N-L CAP 6 POS     |
| <br>TE Part # 1586887-1<br>06P UMNL CAP HSG, P/M, GW      | <br>TE Part # 8-794536-1<br>06P UMNL CAP HSG 150C BLK, SPE  | <br>TE Part # 926682-4<br>6P UN-MNL AUFN-GEH             | <br>TE Part # 1969881-1<br>06P UMNL CAP HSG, P/M, GW V0 |



TE Part # 2029369-1  
06P UMNL-II REAR, TW-N-LK-CAP



TE Part # 2029451-1  
06P UMNL SOK HDR ASSY W/O DRNS



TE Part # 350848-6  
06P UMNL PLUG TEST ASSY 94V0



TE Part # 643253-1  
06P UMNL ASSY MOD HSG VO

Also in the Series | Universal MATE-N-LOK



Circular Power Connectors(2)



Connector Caps & Covers(34)



Connector Contacts(209)



Connector Hardware(12)



Connector Seals & Cavity Plugs(27)



Connector Strain Relief(7)



Insertion & Extraction Tools(4)



Rectangular Connector Housings(1)



Rectangular Power Connectors(671)



Standard Circular Connectors(1)

Customers Also Bought



TE Part # 643228-1  
03P UMNL HDR ASSY R/A 94V0





TE Part # 643414-1  
03P UMNL HDR ASSY POL 94V0



TE Part # 1-1825137-5  
A103SYCB04



TE Part # 1721874-5  
OJ-SS-112LMH2-WG



Documents

Product Drawings

06P UMNL HDR ASSY POL 94VO

English

CAD Files

Customer View Model

ENG\_CVM\_643424-1\_H.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_643424-1\_H.3d\_stp.zip

English

3D PDF

English

Customer View Model

ENG\_CVM\_643424-1\_H.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_SOCKET\_CONNECTORS\_STANDARD\_DENSITY

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English