

TE Internal #: 487223-5

FFC Connectors, Housing, Wire-to-Board, 20 Position, 2.54 mm [.1 in] Centerline, 2 Row, Socket, Package, Normal, Mating Alignment,

Straight, Black

View on TE.com >




Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FFC Connectors > 2.54mm FFC Connectors Receptacle Housing











FFC Connector Product Type: Housing

Connector System: Wire-to-Board

Number of Positions: 20

Centerline (Pitch): 2.54 mm [.1 in]

Number of Rows: 2

All 2.54mm FFC Connectors Receptacle Housing (143)

#### **Features**

### **Product Type Features**

| Connector & Housing Type              | Receptacle    |
|---------------------------------------|---------------|
| Connector & Contact Terminates To     | Wire & Cable  |
| FFC Connector Product Type            | Housing       |
| Connector System                      | Wire-to-Board |
| Insertion Force Type                  | Normal        |
| Configuration Features                |               |
| Number of Positions                   | 20            |
| Number of Rows                        | 2             |
| Electrical Characteristics            |               |
| Dielectric Withstanding Voltage (Max) | 720 VAC       |
| Insulation Resistance                 | 5000 ΜΩ       |
| Operating Voltage                     | 300 VAC       |



## **Body Features**

| Primary Product Color | Black |
|-----------------------|-------|
| Contact Features      |       |

Socket

## Mechanical Attachment

Contact Type

| Mating Alignment Type   | Polarization               |
|-------------------------|----------------------------|
| Mating Retention        | Without                    |
| Mating Alignment        | With                       |
| Panel Mount Feature     | Without                    |
| Connector Mounting Type | Cable Mount (Free-Hanging) |

## **Housing Features**

| Housing Material   | Thermoplastic  |
|--------------------|----------------|
| Centerline (Pitch) | 2.54 mm[.1 in] |
| FFC Cable Entry    | Straight       |

#### **Dimensions**

| Row-to-Row Spacing | 2.54 mm[.1 in] |
|--------------------|----------------|
| 1 9                |                |

## **Usage Conditions**

| Operating remperature range -03 - 103 C[-03 - 221 F] |  | -65 - 105 °C[-85 - 221 °F] | Operating Temperature Range |
|--|--|----------------------------|-----------------------------|
|--|--|----------------------------|-----------------------------|

# Operation/Application

| Circuit Application | Signal |  |
|---------------------|--------|--|
|                     |        |  |

# Industry Standards

| III Flammability Pating | UL 94V-0 |
|-------------------------|----------|
| UL Flammability Rating  | OL 74V-U |

# **Packaging Features**

| Packaging Quantity | 1       |
|--------------------|---------|
| Packaging Method   | Package |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant                               |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant                               |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |



| Halogen Content  Not Low Halogen - contains Br or Cl > 900 ppm. | EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
|---|--|---|
|   | Halogen Content                        |   |

Solder Process Capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # CAT-F439-S01339127

1.27mm FFC Connectors Socket
Contacts






Not applicable for solder process capability


















# Customers Also Bought







# **Documents**

# Product Drawings

020 HOUSING FFC RCPT 100CL DR

English

# **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_487223-5\_P.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_487223-5\_P.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_487223-5\_P.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

#### **Product Specifications**

**Application Specification** 

English

#### **Instruction Sheets**

Instruction Sheet (U.S.)

English

**Extraction Tools** 

FFC Connectors, Housing, Wire-to-Board, 20 Position, 2.54 mm [.1 in] Centerline, 2 Row, Socket, Package, Normal, Mating Alignment, Straight, Black



English

Agency Approvals

Agency Approval Document

English