



Connectors > Connector Accessories > Connector Seals & Cavity Plugs > CPC Heat Shrink Strain Reliefs



Connector Seal & Plug Type: **Cable Seal**
Primary Product Color: **Black**
Operating Temperature (Max): **110 °C [230 °F]**
Operating Temperature Range: **-55 - 110 °C [-67 - 230 °F]**

[All CPC Heat Shrink Strain Reliefs \(7\)](#)

Features

Product Type Features

Connector Seal & Plug Type	Cable Seal
----------------------------	------------

Body Features

Primary Product Color	Black
-----------------------	-------

Mechanical Attachment

Thread Size	.625-24 UNEF-2B
-------------	-----------------

Dimensions

Compatible Cable Diameter Range	6.35 - 15.24 mm [.25 - .6 in]
---------------------------------	-------------------------------

Usage Conditions

Operating Temperature (Max)	110 °C[230 °F]
Operating Temperature Range	-55 - 110 °C[-67 - 230 °F]

Packaging Features

Packaging Quantity	50
Packaging Method	Carton



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # CAT-AM71-C83998M
CPC Connectors, Series 2



TE Part # CAT-AM71-C83998Y
One-Piece Connector, Sealed, CPC Series 1









TE Part # CAT-AM71-C83998K
Circular Connector, Environmentally Sealed, CPC Series 6



TE Part # 206516-1
CPC PLUG ASSEMBLY SIZE 11-4




Also in the Series | AMP CPC



Customers Also Bought





Documents

Product Drawings

CPC STRAIN RELIEF,SIZE 11

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_54010-1_AC.3d_igs.zip

English

Customer View Model

ENG_CVM_54010-1_AC.3d_stp.zip

English

Customer View Model

ENG_CVM_54010-1_AC.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_54010-1_AB.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_54010-1_AB.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_54010-1_AB.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications Continued

English

Product Specifications

Application Specification

English



Instruction Sheets

Instruction Sheet (U.S.)

English