#### VAL-U-LOK

TE Internal #: 1586314-1

Pin Contact, Tin, 600 VAC, 24 - 18 AWG Wire Size, .2 - .8 mm<sup>2</sup> Wire

Size, Crimp, Brass, Power, -40 - 221 °F [-40 - 105 °C]

View on TE.com >



Connectors > Contacts > Connector Contacts











Contact Type: Pin

Contact Mating Area Plating Material: Tin

Wire Contact Termination Area Plating Material: Pre-Tin

Operating Voltage: 600 VAC

Contact Retention Within Housing: With

# **Features**

## **Electrical Characteristics**

Operating Voltage	600 VAC
Contact Features	
Mating Square Post Dimension	1.14 mm[.045 in]
Contact Fabrication	Stamped & Formed
Wire Contact Termination Area Plating Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Type	Pin
Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Pre-Tin
Contact Retention Within Housing	With
Contact Base Material	Brass
Contact Current Rating (Max)	9 A

### **Termination Features**



Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Compatible Insulation Diameter Range	1.5 - 2.4 mm[.06094 in]
Wire Size	.28 mm²
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
Compatible With Agency/Standards Products	CSA, UL
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**






# Customers Also Bought

















## **Documents**

### **Product Drawings**

VAL-U-LOK PIN BR TN 22-18 LP

English

### **CAD Files**

Customer View Model ENG\_CVM\_1586314-1\_C.3d\_igs.zip

English

Pin Contact, Tin, 600 VAC, 24 - 18 AWG Wire Size, .2 - .8 mm² Wire Size, Crimp, Brass, Power, -40 - 221 °F [-40 - 105 °C]



**Customer View Model** 

ENG\_CVM\_1586314-1\_C.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_1586314-1\_C.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

English

**Product Specifications** 

**Application Specification** 

English