
1-1827862-0 - ACTIVE

Dynamic Series | Dynamic 1000 Series

TE Internal #: 1-1827862-0 Housing, Receptacle, Wire-to-Board, 20 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 1000 Series

View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings >



Receptacle and Tab Housing: 2.0 mm pitch, 125V

Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 20

Centerline (Pitch): 2 mm [.079 in]

All Receptacle and Tab Housing: 2.0 mm pitch, 125V (53)



Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	20
Number of Rows	2
Body Features	
Primary Product Color	Black
Termination Features	

C For support call +1 800 522 6752

05/28/2024 04:51PM |Page 1

1-1827862-0

Housing, Receptacle, Wire-to-Board, 20 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 1000 Series



Termination Method to Wire & Cable	Crimp	
Mechanical Attachment		
Mating Retention	With	
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Centerline (Pitch)	2 mm[.079 in]	
Dimensions		
Row-to-Row Spacing	3.3 mm[.129 in]	
Usage Conditions		
Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]	
Operation/Application		
Circuit Application	Signal	
Product Compliance		
For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	
Solder Process Capability	Not applicable for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

1-1827862-0

Housing, Receptacle, Wire-to-Board, 20 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 1000 Series



Compatible Parts




TE Part # CAT-D9934-A15E Header Assembly: Wire-to-Board, 3A, Gold or Tin Plated




TE Part # 1-2379284-0 D1100 HDR ASSY H 20P XBLACK PRE-TIN



Also in the Series | Dynamic 1000 Series





Customers Also Bought

TE Part # 1-1903128-4 Receptacle and Tab Housing: 2.0 mm pitch, 125V	TE Part # 2-917809-3 DYNAMIC D-5 TAB HSG D/R 6P Y-Y	TE Part # 2-1318118-9 DYNAMIC D2100 REC HSG 20P Y	TE Part # 1-1827864-3 DYNAMIC 1200D REC HSG 6P X BLACK

1-1827862-0

Housing, Receptacle, Wire-to-Board, 20 Position, .079 in [2 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 1000 Series





Documents

Product Drawings DYNAMIC 1100D REC HSG 20P X BLACK

Japanese

CAD Files

Customer View Model ENG_CVM_CVM_1-1827862-0_K.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1827862-0_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1827862-0_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Product Specifications Application Specification

English

Instruction Sheets Instruction Sheet (non U.S.)

English

Agency Approvals TUV Certificate

English