TE Internal #: 2023246-2

SATA, Receptacle, Cable-to-Board, 22 Position, 7P + 15P, Standard Profile, Right Angle, Surface Mount, 1 Row, 2 Port, Top, .05 in [1.27]

mm] Centerline

View on TE.com >



Connectors > Audio & Video Connectors > SATA & Micro SATA











SATA Connector Type: SATA

Connector & Housing Type: Receptacle
Connector System: Cable-to-Board

Number of Positions: 22

Contact Configuration: **7P + 15P** 

## **Features**

## Product Type Features

SATA Connector Type	SATA
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

#### Configuration Features

Number of Positions	22
PCB Mount Orientation	Right Angle
Number of Rows	1
Number of Ports	2

## **Body Features**

Connector Profile	Standard

### **Contact Features**

Contact Mating Area Plating Material Thickness	.3 μm[12 μin]
Contact Mating Area Plating Material	Gold



PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Configuration	7P + 15P
Contact Current Rating (Max)	1.5 A
Termination Features	
Termination Post & Tail Length	1.3 mm[.05 in]
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
PCB Mount Retention Feature Length	1.9 mm[.075 in]
Mating Alignment Type	Polarization
PCB Mount Retention	With
PCB Mount Retention Type	Solder Peg
PCB Mount Location	Тор
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Centerline (Pitch)	1.27 mm[.05 in]
Dimensions	
PCB Thickness (Recommended)	1.2 mm[.048 in]
Profile Height from PCB	5.2 mm[.205 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	30
Packaging Method	Box & Tray, Tray

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# **Customers Also Bought**






















## **Documents**

**Product Drawings** 

ASS'Y SATA REC. R/A SMT TYPE 3.45H

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2023246-2\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2023246-2\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2023246-2\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

**Product Specifications** 

SATA, Receptacle, Cable-to-Board, 22 Position, 7P + 15P, Standard Profile, Right Angle, Surface Mount, 1 Row, 2 Port, Top, .05 in [1.27 mm] Centerline



## **Product Specification**

English