

AMP | Timer Connector System

TE Internal #: 1-963226-1

Housing for Female Terminals, Wire-to-Wire, 42 Position, .157 in [4 mm] Centerline, Black, Wire & Cable, Power, Timer Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector System: Wire-to-Wire

Number of Positions: 42

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4 mm [.157 in]

Sealable: No

All Timer Connector Housing (518)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	42
Number of Rows	3
Electrical Characteristics	
Nominal Voltage Architecture	12 V
Body Features	
Primary Product Color	Black
Connector & Keying Code	A1

Contact Features



Contact Size	1.6mm, 2.8mm
Contact Type	Receptacle
Mating Tab Width	1.6 mm, 2.8 mm[.063 in][.11 in]
Contact Current Rating (Max)	22 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]
Dimensions	
Connector Height	33 mm[1.299 in]
Product Width	30.5 mm[1.201 in]
Product Length	77.2 mm[3.039 in]
Row-to-Row Spacing	6 mm[.236 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Carton
Other	
Serviceable	No
	No

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | Timer Connector System





Automotive Connector Caps & Covers (14)



Automotive Connector Locks & Position Assurance(15)



Automotive Housings(216)



Automotive Terminals(136)



Connector Seals & Cavity Plugs(31)




Crimp Terminal Housings(13)



Insertion & Extraction Tools(18)



Other Automotive Connector Accessories(1)



PCB Headers & Receptacles(77)



Quick Disconnects(4)

Customers Also Bought



TE Part # 1-1564414-1 12POS,TAB 1.6X0.6,TAB HSG,ASSY



TE Part # 2-963217-1 16 J-P-T GEH KOMPL



TE Part # 60773-2 SPADE TERMINAL 18-14 AWG TPBR



TE Part # NB10036001 ATUM-24/6-0-45MM




TE Part # 321873
BODY SOLIS RING 2/0 1/2



TE Part # 929938-1

JPT REC 2.8 Contact SWS Sn (LP)



TE Part # 963711-2 MICRO TIM RECEPTACLE CONTACT



Documents

Housing for Female Terminals, Wire-to-Wire, 42 Position, .157 in [4 mm] Centerline, Black, Wire & Cable, Power, Timer Connector System



Product Drawings

42P SOCKET HOUSING MIX KPL

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-963226-1_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-963226-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-963226-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

Timer Interconnection System

English