

Sensors > Humidity Sensors > Humidity Sensor Assemblies > Digital RH Temperature Pressure Sensor



Humidity Sensor Product Type: **RHTP**

Supply Voltage (Peak): **32 VDC**

Operating Temperature Range: **-40 - 105 °C [-40 - 221 °F]**

Accuracy: **±3 %RH**

Current Consumption: **25 mA**

[All Digital RH Temperature Pressure Sensor \(5\)](#)

Features

Product Type Features

Humidity Sensor Product Type	RHTP
Interface Signal Type	Digital

Electrical Characteristics

Supply Voltage (Peak)	32 VDC
Current Consumption	25 mA

Signal Characteristics

Baud Rate	250 Kb/s
Transmit Rate	100 msec

Usage Conditions

Humidity Operating Range	0 - 100 %RH
Operating Temperature Range	-40 - 105 °C [-40 - 221 °F]
Accuracy	±3 %RH

Operation/Application

Pressure (Max)	130 kPa
----------------	---------

Other

Response Time	5 seconds
---------------	-----------

Product Compliance

For compliance documentation, visit the product page on [TE.com](https://www.te.com/compliance)>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (85% in Solder) <small>Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.</small>
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # CAT-HSA0004
Digital RH Temperature Pressure Sensor


TE Part # FPP800A110
FPS2800B12C4 STD

Also in the Series | [MEAS HTD](#)



Humidity Sensor Assemblies(3)

Customers Also Bought

TE Part # T4171010005-001
M12,REAR MOUNTING,MALE,A,5P,0.2
M WIRETE Part # 7-520366-2
ULTRAFAST 110 ASSY REC 26-22
TPBR LPTE Part # 2238236-1
SPLICE, AMPLIVAR, PIGTAIL, 2D, 600-7000TE Part # 2317656-5
AV25 SPM 3A MOVING RING
YELLOW 12VTE Part # HPP845E031R5
I.C 21D RH/T B5000TE Part # 173716-2
040 HDIO REC CONTTE Part # K1002915
Toggle Switch 08-1-1-14TE Part # 140723-2
SPLICE 22-16 AWG .02 TPBRTE Part # 62201-2
SPLC AMVAR 3000-7000 .020TPBRTE Part # AS614-35SA
PLUG.BOOT TERMIN.N TYPE 6

Documents

CAD Files

[3D PDF](#)
[3D](#)

Customer View Model

[ENG_CVM_CVM_HPP816E056_A.2d_dxf.zip](#)
[English](#)

Customer View Model

[ENG_CVM_CVM_HPP816E056_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_HPP816E056_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Data sheet TRICAN HTD2800Px B11C6V2](#)

English